Help

```
#include <stdlib.h>
#include  "
href../../../mod/bs1d/bs1d_std/bs1d_std_h_src.pdfbs1d_std.h"
#include "
href../../../common/error_msg_h_src.pdferror_msg.h"
#include "
href../../../common/enums_h_src.pdfenums.h"

static double *Q = NULL, *Weights = NULL, *Trans = NULL, *Price = NULL;
static double *Aux_Path = NULL, *Aux_Stock = NULL, *Aux_BS = NULL;
static double *Sigma = NULL;
static int *Path_Int = NULL;

static int RaQ_Allocation(int AL_T_Size, int BS_Dimension,
                          int OP_Exercice_Dates)
{
  if (Q == NULL)
    Q = malloc(AL_T_Size * OP_Exercice_Dates * BS_Dimension * sizeof(double));
  if (Q == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Trans == NULL)
    Trans = malloc(OP_Exercice_Dates * AL_T_Size * AL_T_Size * sizeof(double));
  if (Trans == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Weights == NULL)
    Weights = malloc(OP_Exercice_Dates * AL_T_Size * sizeof(double));
  if (Weights == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Price == NULL)
    Price = malloc(OP_Exercice_Dates * AL_T_Size * sizeof(double));
  if (Price == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Aux_Path == NULL)
    Aux_Path = malloc(OP_Exercice_Dates * BS_Dimension * sizeof(double));
  if (Aux_Path == NULL)
```

```
    return MEMORY_ALLOCATION_FAILURE;

  if (Aux_Stock == NULL)
    Aux_Stock = malloc(BS_Dimension * sizeof(double));
  if (Aux_Stock == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Aux_BS == NULL)
    Aux_BS = malloc(BS_Dimension * sizeof(double));
  if (Aux_BS == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Sigma == NULL)
    Sigma = malloc(BS_Dimension * BS_Dimension * sizeof(double));
  if (Sigma == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  if (Path_Int == NULL)
    Path_Int = malloc(OP_Exercice_Dates * sizeof(int));
  if (Path_Int == NULL)
    return MEMORY_ALLOCATION_FAILURE;

  return OK;
}

static void RaQ_Liberation()
{
  if (Q != NULL)
    {
      free(Q);
      Q = NULL;
    }
  if (Trans != NULL)
    {
      free(Trans);
      Trans = NULL;
    }
  if (Weights != NULL)
    {
      free(Weights);
      Weights = NULL;
```

```
    }
  if (Price != NULL)
    {
      free(Price);
      Price = NULL;
    }
  if (Aux_Path != NULL)
    {
      free(Aux_Path);
      Aux_Path = NULL;
    }
  if (Aux_Stock != NULL)
    {
      free(Aux_Stock);
      Aux_Stock = NULL;
    }

  if (Aux_BS != NULL)
    {
      free(Aux_BS);
      Aux_BS = NULL;
    }

  if (Sigma != NULL)
    {
      free(Sigma);
      Sigma = NULL;
    }
  if (Path_Int != NULL)
    {
      free(Path_Int);
      Path_Int = NULL;
    }
  return;
}

static int NearestCell(int Time, int AL_T_Size, long OP_EmBS_Di, int BS_Dimensio
{
  int j, k, l = 0;
  double  min = DBL_MAX, aux, auxnorm;
  for (j = 0; j < AL_T_Size; j++)
```

```
    {
      aux = 0;
      for (k = 0; k < BS_Dimension; k++)
        {
          auxnorm = Aux_Path[Time * BS_Dimension + k] -
                    Q[(long)j * OP_EmBS_Di + Time * BS_Dimension + k];
          aux += auxnorm * auxnorm;
        }
      if (min > aux)
        {
          min = aux;
          l = j;
        }
    }
  return l;
}

static void ForwardPath(double *Path, double *Initial_Stock, int Initial_Time, i
{
  int i, j, k;
  double aux;
  double *SigmapjmBS_Dimensionpk;

  for (j = 0; j < BS_Dimension; j++) Path[Initial_Time * BS_Dimension + j] = Ini

  for (i = Initial_Time + 1; i < Initial_Time + Number_Dates; i++)
    {
      for (j = 0; j < BS_Dimension; j++)
        {
          Aux_Stock[j] = Sqrt_Step * pnl_rand_normal(generator);
        }
      SigmapjmBS_Dimensionpk = Sigma;


      for (j = 0; j < BS_Dimension; j++)
        {
          aux = 0.;
          for (k = 0; k <= j; k++)
            {
              aux += (*SigmapjmBS_Dimensionpk) * Aux_Stock[k];
              SigmapjmBS_Dimensionpk++;
```

```
            }
          SigmapjmBS_Dimensionpk += BS_Dimension - j - 1;
          aux -= Step * Aux_BS[j];
          Path[i * BS_Dimension + j] = Path[(i - 1) * BS_Dimension + j] * exp(au
        }
    }
}

static double Discount(double Time, double BS_Interest_Rate)
{
  return exp(-BS_Interest_Rate * Time);
}

static void Init_Tesselations(long AL_MonteCarlo_Iterations, int AL_T_Size, int
{
  int i, j, k, Vimoins, Vi;
  long l;
  long OP_ExmBS_Di = (long)OP_Exercice_Dates * BS_Dimension;

  /* Random Quantizers */
  for (i = 0; i < AL_T_Size; i++)
    ForwardPath(Q + i * OP_Exercice_Dates * BS_Dimension, BS_Spot, 0, OP_Exercic
                generator, BS_Dimension, Step, Sqrt_Step);

  /* Weights and Transitions */
  for (i = 0; i < OP_Exercice_Dates; i++)
    for (j = 0; j < AL_T_Size; j++)
      Weights[i * AL_T_Size + j] = 0;

  for (i = 0; i < OP_Exercice_Dates; i++)
    for (j = 0; j < AL_T_Size; j++)
      for (k = 0; k < AL_T_Size; k++)
        Trans[i * AL_T_Size * AL_T_Size + j * AL_T_Size + k] = 0;

  for (l = 0; l < AL_MonteCarlo_Iterations - AL_T_Size; l++)
    {

      /*Black-Sholes Paths from time 0 to maturity*/
      ForwardPath(Aux_Path, BS_Spot, 0, OP_Exercice_Dates, generator, BS_Dimensi

      Vimoins = 0;
```

```
      for (i = 1; i < OP_Exercice_Dates; i++)
        {
          Vi = NearestCell(i, AL_T_Size, OP_ExmBS_Di, BS_Dimension);
          Weights[i * AL_T_Size + Vi] += 1;
          Trans[i * AL_T_Size * AL_T_Size + Vimoins * AL_T_Size + Vi] += 1;
          Vimoins = Vi;
        }
    }
  Weights[0] = AL_MonteCarlo_Iterations - AL_T_Size;
  for (i = 1; i < OP_Exercice_Dates; i++)
    for (j = 0; j < AL_T_Size; j++)
      if (Weights[(i - 1)*AL_T_Size + j] > 0)
        for (k = 0; k < AL_T_Size; k++)
          Trans[i * AL_T_Size * AL_T_Size + j * AL_T_Size + k] /= Weights[(i - 1
}


static void RaQ(double *PrixDir, long MC_Iterations, NumFunc_1 *p, int size, int
{
  int i, j, k, BS_Dimension = 1;
  long l;
  double step, Sqrt_Step, DiscountStep, aux, AL_BPrice, AL_FPrice;
  AL_FPrice = 0.0;
  *PrixDir = 0.;
  step = t / (exercise_date_number - 1.);
  Sqrt_Step = sqrt(step);
  DiscountStep = exp(-r * step);

  /*Memory Allocation*/
  RaQ_Allocation(size, BS_Dimension, exercise_date_number);

  /*Black-Sholes initalization parameters*/
  *Sigma = sigma;
  Aux_BS[0] = 0.5 * SQR(sigma) - r + divid;

  /* Cells Weights and Transitions probabilities   */
  Init_Tesselations(MC_Iterations, size, exercise_date_number, generator, BS_Dim


  for (i = 0; i < size; i++)
    Price[(exercise_date_number - 1)*size + i] = 0;
```

```
/* Dynamical programing (backward price)*/
for (i = exercise_date_number - 2; i >= 1; i--)
  {
    for (j = 0; j < size; j++)
      {
        aux = 0;

        /*Payoff control variate*/
        for (k = 0; k < size; k++)
          {
            aux += (Price[(i + 1) * size + k] + (p->Compute)(p->Par, *(Q + k *
                   Trans[(i + 1) * size * size + j * size + k];
          }
        aux *= DiscountStep;
        aux -= (p->Compute)(p->Par, *(Q + j * exercise_date_number * BS_Dimens
        Price[i * size + j] = MAX(0., aux);
      }
  }


aux = 0;
for (k = 0; k < size; k++)
  aux += (Price[size + k] + (p->Compute)(p->Par, *(Q + k * exercise_date_numbe
                                          BS_Dimension))) * Trans[size * size +
/*Backward Price*/
aux *= DiscountStep;
if (!gj_flag)
  AL_BPrice = MAX((p->Compute)(p->Par, s_vector[0]), aux);
else AL_BPrice = aux;

/* Forward price */
for (k = 0; k < size; k++)
  {
    Price[k] = AL_BPrice - (p->Compute)(p->Par, s_vector[0]);
  }

for (j = 0; j < size; j++)
  {
    i = -1;
    do
```

```
        {
          i++;
        }
      while (0 < Price[i * size + j]);

      AL_FPrice += Discount((double)i * step, r) * (Price[i * size + j] + (p->Co
    }

  for (l = 0; l < MC_Iterations - size; l++)
    {
      ForwardPath(Aux_Path, s_vector, 0, exercise_date_number, generator, BS_Dim
      Path_Int[0] = 0;
      for (i = 1; i < exercise_date_number; i++)
        {
          Path_Int[i] = NearestCell(i, size, exercise_date_number *
                                    BS_Dimension, BS_Dimension);
        }

      i = -1;
      do
        {
          i++;
        }
      while (0 < Price[i * size + Path_Int[i]]);
      AL_FPrice += Discount((double)i * step, r) * (Price[i * size + Path_Int[i]
    }
  AL_FPrice /= (double)MC_Iterations;

  /*Price = Mean of Forward and Backward Price*/
  *PrixDir = 0.5 * (AL_FPrice + AL_BPrice);

  /*Memory Disallocation*/
  if (Fermeture)
    RaQ_Liberation();

  return;

}

static int MCRandomQuantization(double s, NumFunc_1  *p, double t, double r, dou
{
```

```
double p1, p2, p3;
int simulation_dim = 1, fermeture = 1, init_mc;
double s_vector[1];
double s_vector_plus[1];

/*Initialisation*/
s_vector[0] = s;
s_vector_plus[0] = s * (1. + inc);

/*MC sampling*/
init_mc = pnl_rand_init(generator, simulation_dim, N);

/* Test after initialization for the generator */
if (init_mc == OK)
  {

    /*Geske-Johnson Formulae*/
    if (exercise_date_number == 0)
      {
        RaQ(&p1, N, p, size_tesselation, fermeture, generator, 2, s_vector, t,
        RaQ(&p2, N, p, size_tesselation, fermeture, generator, 3, s_vector, t,
        RaQ(&p3, N, p, size_tesselation, fermeture, generator, 4, s_vector, t,
        *ptprice = p3 + 7. / 2.*(p3 - p2) - (p2 - p1) / 2.;
      }
    else
      {
        RaQ(ptprice, N, p, size_tesselation, fermeture, generator, exercise_da
      }

    /*Delta*/
    init_mc = pnl_rand_init(generator, simulation_dim, N);

    if (exercise_date_number == 0)
      {
        RaQ(&p1, N, p, size_tesselation, fermeture, generator, 2, s_vector_plu
        RaQ(&p2, N, p, size_tesselation, fermeture, generator, 3, s_vector_plu
        RaQ(&p3, N, p, size_tesselation, fermeture, generator, 4, s_vector_plu
        *ptdelta = ((p3 + 7. / 2.*(p3 - p2) - (p2 - p1) / 2.) - *ptprice) / (s
      }
```

```
      else
        {
          RaQ(&p1, N, p, size_tesselation, fermeture, generator, exercise_date_n
          *ptdelta = (p1 - *ptprice) / (s * inc);
        }
    }
  return init_mc;
}

int CALC(MC_RandomQuantization)(void *Opt, void *Mod, PricingMethod *Met)
{
  TYPEOPT *ptOpt = (TYPEOPT *)Opt;
  TYPEMOD *ptMod = (TYPEMOD *)Mod;
  double r, divid;

  r = log(1. + ptMod->R.Val.V_DOUBLE / 100.);
  divid = log(1. + ptMod->Divid.Val.V_DOUBLE / 100.);

  return MCRandomQuantization(ptMod->S0.Val.V_PDOUBLE,
                              ptOpt->PayOff.Val.V_NUMFUNC_1,
                              ptOpt->Maturity.Val.V_DATE - ptMod->T.Val.V_DATE,
                              r,
                              divid,
                              ptMod->Sigma.Val.V_PDOUBLE,
                              Met->Par[0].Val.V_LONG,
                              Met->Par[1].Val.V_ENUM.value,
                              Met->Par[2].Val.V_PDOUBLE,
                              Met->Par[3].Val.V_INT,
                              Met->Par[4].Val.V_INT,
                              &(Met->Res[0].Val.V_DOUBLE),
                              &(Met->Res[1].Val.V_DOUBLE));
}

static int CHK_OPT(MC_RandomQuantization)(void *Opt, void *Mod)
{
  Option *ptOpt = (Option *)Opt;
  TYPEOPT *opt = (TYPEOPT *)(ptOpt->TypeOpt);

  if ((opt->EuOrAm).Val.V_BOOL == AMER)
    return OK;
  else
```

```
    return WRONG;
}

static int MET(Init)(PricingMethod *Met, Option *Opt)
{
  if (Met->init == 0)
    {
      Met->init = 1;
      Met->Par[0].Val.V_LONG = 20000;
      Met->Par[1].Val.V_ENUM.value = 0;
      Met->Par[1].Val.V_ENUM.members = &PremiaEnumMCRNGs;
      Met->Par[2].Val.V_PDOUBLE = 0.01;
      Met->Par[3].Val.V_INT = 20;
      Met->Par[4].Val.V_INT = 150;

    }
  return OK;
}



PricingMethod MET(MC_RandomQuantization) =
{
  "MC_RandomQuantization",
  { {"N iterations", LONG, {100}, ALLOW},
    {"RandomGenerator", ENUM, {100}, ALLOW},
    {"Delta Increment Rel", PDOUBLE, {100}, ALLOW},
    {"Number of Exercise Dates (0->Geske Johnson Formulae", INT, {100}, ALLOW},
    {"Tesselation Size", INT, {100}, ALLOW},
    {" ", PREMIA_NULLTYPE, {0}, FORBID}
  },
  CALC(MC_RandomQuantization),
  { {"Price", DOUBLE, {100}, FORBID},
    {"Delta", DOUBLE, {100}, FORBID} ,
    {" ", PREMIA_NULLTYPE, {0}, FORBID}
  },
  CHK_OPT(MC_RandomQuantization),
  CHK_mc,
  MET(Init)
};
```