

## [Help](#)

```
#include <stdlib.h>
#include "
href../../mod/bs1d/bs1d_doublim/bs1d_doublim_h_src.pdfbs1d_doublim.h"
#include "
href../../common/error_msg_h_src.pdferror_msg.h"

static int Psor_In(double s, NumFunc_1 *L, NumFunc_1 *U, NumFunc_1 *Rebate, N
{
    int      Index, PriceIndex, TimeIndex;
    int      j, loops;
    double   k, vv, h, z, alpha, beta, gamma, y, alpha1, beta1, gamma1, down, upwi
    double   error, norm, x, up, rebate, l, u, pricenh, pricen2h, priceph;
    double   *P, *Obst, *Rhs;

    /*Memory Allocation*/
    P = malloc((N + 2) * sizeof(double));
    if (P == NULL)
        return MEMORY_ALLOCATION_FAILURE;
    Obst = malloc((N + 2) * sizeof(double));
    if (Obst == NULL)
        return MEMORY_ALLOCATION_FAILURE;
    Rhs = malloc((N + 2) * sizeof(double));
    if (Rhs == NULL)
        return MEMORY_ALLOCATION_FAILURE;

    /*Time Step*/
    k = t / (double)M;

    /*Space Step*/
    u = (U->Compute)(U->Par, 0);
    l = (L->Compute)(L->Par, 0);
    rebate = (Rebate->Compute)(Rebate->Par, 0);
    x = log(s);
    down = log(l);
    up = log(u);
    h = (up - down) / (double)(N + 1);

    /*Coefficient of diffusion augmented*/
    vv = 0.5 * sigma * sigma;
```

```

z = (r - divid) - vv;
if ((h * fabs(z)) <= vv)
    upwind_alphacoef = 0.5;
else
{
    if (z > 0.) upwind_alphacoef = 0.0;
    else upwind_alphacoef = 1.0;
}
vv -= z * h * (upwind_alphacoef - 0.5);

/*Lhs factor of theta-schema*/
alpha = theta * k * (-vv / (h * h) + z / (2.0 * h));
beta = 1.0 + k * theta * (r + 2.*vv / (h * h));
gamma = k * theta * (-vv / (h * h) - z / (2.0 * h));

/*Rhs factor of theta-schema*/
alpha1 = k * (1.0 - theta) * (vv / (h * h) - z / (2.0 * h));
beta1 = 1.0 - k * (1.0 - theta) * (r + 2.*vv / (h * h));
gamma1 = k * (1.0 - theta) * (vv / (h * h) + z / (2.0 * h));

/*Terminal Values*/
for (PriceIndex = 1; PriceIndex <= N; PriceIndex++)
{
    Obst[PriceIndex] = (p->Compute)(p->Par, exp(down + (double)PriceIndex * h)
    P[PriceIndex] = rebate;
}
P[0] = (p->Compute)(p->Par, 1);
P[N + 1] = (p->Compute)(p->Par, u);

/*Finite Difference Cycle*/
for (TimeIndex = 1; TimeIndex <= M; TimeIndex++)
{
    /*Init Rhs*/
    for (j = 1; j <= N; j++)
        Rhs[j] = alpha1 * P[j - 1] + beta1 * P[j] + gamma1 * P[j + 1];

    P[0] = Boundary(l, p, (double)TimeIndex * k, r, divid, sigma);
    P[N + 1] = Boundary(u, p, (double)TimeIndex * k, r, divid, sigma);

    /*Psor Cycle*/
    loops = 0;

```

```

do
{
    error = 0.;
    norm = 0.;

    for (j = 1; j <= N; j++)
    {
        y = (Rhs[j] - alpha * P[j - 1] - gamma * P[j + 1]) / beta;
        y = MAX(Obst[j], P[j] + omega * (y - P[j]));

        error += (double)(j + 1) * fabs(y - P[j]);
        norm += fabs(y);
        P[j] = y;
    }

    if (norm < 1.0) norm = 1.0;
    error = error / norm;

    loops++;
}
while ((error > epsilon) && (loops < MAXLOOPS));
}
Index = (int)floor((x - down) / h);

/*Price*/
if ((x == up) && (x == down))
    *ptprice = P[0];
else
    *ptprice = P[Index] + (P[Index + 1] - P[Index]) * (exp(x) - exp(down + Index));

/*Delta*/
if ((x == up) && (x == down))
    *ptdelta = 0.0;
else
{
    pricenh = P[Index + 1] + (P[Index + 2] - P[Index + 1]) * (exp(x + h) - exp(down + Index + h));
    if (Index > 0)
    {
        priceph = P[Index - 1] + (P[Index] - P[Index - 1]) * (exp(x - h) - exp(down + Index - h));
        *ptdelta = (pricenh - priceph) / (2 * s * h);
    }
}

```

```

        else
        {
            pricen2h = P[Index + 2] + (P[Index + 3] - P[Index + 2]) * (exp(x + 2 *
            *ptdelta = (4 * pricenh - pricen2h - 3 * (*ptprice)) / (2 * s * h);
        }
    }

    /*Memory Desallocation*/
    free(P);
    free(Obst);
    free(Rhs);

    return OK;
}

int CALC(FD_Psor_In)(void *Opt, void *Mod, PricingMethod *Met)
{
    TYPEOPT *ptOpt = (TYPEOPT *)Opt;
    TYPEMOD *ptMod = (TYPEMOD *)Mod;
    double r, divid;

    r = log(1. + ptMod->R.Val.V_DOUBLE / 100.);
    divid = log(1. + ptMod->Divid.Val.V_DOUBLE / 100.);

    return Psor_In(ptMod->S0.Val.V_PDOUBLE, ptOpt->LowerLimit.Val.V_NUMFUNC_1, ptO

}

static int CHK_OPT(FD_Psor_In)(void *Opt, void *Mod)
{
    Option *ptOpt = (Option *)Opt;
    TYPEOPT *opt = (TYPEOPT *) (ptOpt->TypeOpt);

    if ((opt->TwoDoubleStep).Val.V_BOOL == FALSE)
        if ((opt->Parisian).Val.V_BOOL == FALSE)
            if ((strcmp(((Option *)Opt)->Name, "DoubleCallInAmer") == 0) || (strcmp(((
                return OK;
    return WRONG;
}

static int MET(Init)(PricingMethod *Met, Option *Opt)
{

```

```

if (Met->init == 0)
{
    Met->init = 1;

    Met->Par[0].Val.V_INT2 = 100;
    Met->Par[1].Val.V_INT2 = 100;
    Met->Par[2].Val.V_RGDOUBLE = 0.5;
    Met->Par[3].Val.V_RGDOUBLE = 1.5;
    Met->Par[4].Val.V_RGDOUBLE = 1.0e-7;

}

return OK;
}

PricingMethod MET(FD_Psor_In) =
{
    "FD_Psor_In",
    { {"SpaceStepNumber", INT2, {100}, ALLOW    }, {"TimeStepNumber", INT2, {100},
        {"Theta", RGDOUBLE051, {100}, ALLOW}, {"Omega", RGDOUBLE12, {100}, ALLOW}, {
    },
    CALC(FD_Psor_In),
    {"Price", DOUBLE, {100}, FORBID}, {"Delta", DOUBLE, {100}, FORBID} , {" ", PR
    CHK_OPT(FD_Psor_In),
    CHK_psor,
    MET(Init)
};

```