Help

```
#include <stdlib.h>
#include  "
href../../../mod/hullwhite1d/hullwhite1d_stdi/hullwhite1d_stdi_h_src.pdfhullwhit
#include "
href../../../mod/hullwhite1d/hullwhite1d_stdi/hullwhite1d_includes_h_src.pdfhull

//The "#else" part of the code will be freely available after the (year of creat
#if defined(PremiaCurrentVersion) && PremiaCurrentVersion < (2007+2)
int CALC(CF_ReceiverSwaptionHW1D)(void *Opt, void *Mod, PricingMethod *Met)
{
  return AVAILABLE_IN_FULL_PREMIA;
}
static int CHK_OPT(CF_ReceiverSwaptionHW1D)(void *Opt, void *Mod)
{
  return NONACTIVE;
}
#else

///* Computation the function phi used to find the Critical Rate in the Jamishid
static double phi(ZCMarketData *ZCMarket, double r, double periodicity, double o
{
  int i, nb_payement;
  double ci, sum, sum_der, ti;

  double ZCPrice;
  double A_tT, B_tT;

  ZCPrice = 0.;
  A_tT = 0;
  B_tT = 0;
  sum = 0.;
  sum_der = 0.;

  ci = periodicity * SwaptionFixedRate;
  ti = option_maturity;

  nb_payement = (int)((contract_maturity - option_maturity) / periodicity);

  for (i = 1; i <= nb_payement; i++)
```

```
    {
      ti += periodicity;

      ZCPrice_CoefficientHW1D(ZCMarket, a, sigma, option_maturity, ti, &A_tT, &B

      ZCPrice = ZCPrice_Using_CoefficientHW1D(r, A_tT, B_tT);

      sum += ci * ZCPrice;

      sum_der += ci * ZCPrice * (-B_tT);
    }

  sum += ZCPrice;

  sum_der += ZCPrice * (-B_tT);

  return (sum - 1.) / sum_der;
}


///* Computation of Critical Rate in the Jamishidian decomposition, with the new
static double Critical_Rate(ZCMarketData *ZCMarket, double r_initial, double per
{
  double previous, current;
  int nbr_iterations;

  const double precision = 0.0001;

  current = r_initial;
  nbr_iterations = 0;

  do
    {
      nbr_iterations++;
      previous = current;
      current = current - phi(ZCMarket, current, periodicity, option_maturity, c

    }
  while ((fabs(previous - current) > precision) && (nbr_iterations <= 10));

  return current;
```

```
}

///* Payer Swaption price as a combination of ZC Call option prices
static int cf_ps1d(int flat_flag, double r_t, char *curve, double Nominal, doubl
{
  int i, nb_payement;
  double ci, sum , ti;

  double critical_r, Strike_i, CallOptionPrice;
  ZCMarketData ZCMarket;

  CallOptionPrice = 0.; /* to avoid warning */
  /* Flag to decide to read or not ZC bond datas in "initialyields.dat" */
  /* If P(0,T) not read then P(0,T)=exp(-r0*T) */
  if (flat_flag == 0)
    {
      ZCMarket.FlatOrMarket = 0;
      ZCMarket.Rate = r_t;
    }

  else
    {
      ZCMarket.FlatOrMarket = 1;
      ZCMarket.filename = curve;
      ReadMarketData(&ZCMarket);
      r_t = -log(BondPrice(INC, &ZCMarket)) / INC;

      if (contract_maturity > GET(ZCMarket.tm, ZCMarket.Nvalue - 1))
        {
          printf("\ nError : time bigger than the last time value entered in ini
          exit(EXIT_FAILURE);
        }
    }

  ti = option_maturity;
  ci = periodicity * SwaptionFixedRate;

  nb_payement = (int)((contract_maturity - option_maturity) / periodicity);

  critical_r = Critical_Rate(&ZCMarket, r_t, periodicity, option_maturity, contr
```

```
  sum = 0.;

  for (i = 1; i <= nb_payement; i++)
    {
      ti += periodicity;

      Strike_i = cf_hw1d_zcb(&ZCMarket, a, sigma, option_maturity, critical_r, t

      CallOptionPrice = cf_hw1d_zbcall(&ZCMarket, a, sigma, ti, option_maturity,

      sum += ci * CallOptionPrice;
    }

  sum += CallOptionPrice;

  *price = Nominal * sum;

  DeleteZCMarketData(&ZCMarket);

  return OK;
}

int CALC(CF_ReceiverSwaptionHW1D)(void *Opt, void *Mod, PricingMethod *Met)
{
  TYPEOPT *ptOpt = (TYPEOPT *)Opt;
  TYPEMOD *ptMod = (TYPEMOD *)Mod;


  return cf_ps1d(ptMod->flat_flag.Val.V_INT,
                 MOD(GetYield)(ptMod),
                 MOD(GetCurve)(ptMod),
                 ptOpt->Nominal.Val.V_PDOUBLE,
                 ptOpt->ResetPeriod.Val.V_DATE,
                 ptOpt->OMaturity.Val.V_DATE - ptMod->T.Val.V_DATE,
                 ptOpt->BMaturity.Val.V_DATE - ptMod->T.Val.V_DATE,
                 ptOpt->FixedRate.Val.V_PDOUBLE,
                 ptMod->a.Val.V_DOUBLE,
                 ptMod->Sigma.Val.V_PDOUBLE,
                 &(Met->Res[0].Val.V_DOUBLE));
}
static int CHK_OPT(CF_ReceiverSwaptionHW1D)(void *Opt, void *Mod)
```

```
{
  return strcmp(((Option *)Opt)->Name, "ReceiverSwaption");
}
#endif //PremiaCurrentVersion



static int MET(Init)(PricingMethod *Met, Option *Opt)
{
  if (Met->init == 0)
    {
      Met->init = 1;
    }

  return OK;
}

PricingMethod MET(CF_ReceiverSwaptionHW1D) =
{
  "CF_HullWhite1d_ReceiverSwaption",
  {{" ", PREMIA_NULLTYPE, {0}, FORBID}},
  CALC(CF_ReceiverSwaptionHW1D),
  {{"Price", DOUBLE, {100}, FORBID}, {" ", PREMIA_NULLTYPE, {0}, FORBID}},
  CHK_OPT(CF_ReceiverSwaptionHW1D),
  CHK_ok,
  MET(Init)
} ;
```