Help

```
#ifndef __STRUCTS_H__
#define __STRUCTS_H__

/*value of a polynomial function h between x1 and x2,
  y1=h(x1), y2=h(x2). degree is the degree of the polynom
  and a contains its coefficients
*/


/**
 * \ defgroup Polynomial Step Functions
 */
/*@{*/

typedef struct
{
  double                x1;/*!< l.h.s. of an interval */
  double              x2;/*!< r.h.s. of an interval */
  double              y1;/*!< y1=h(x1), where h is a polynomial function */
  double              y2;/*!< y2=h(x2), where h is a polynomial function */
  int                 degree;/*!< degree of the polynom h */
  double              *a;/*!< coefficients of the polynom. Be
                           careful a[0] corresponds to the
                           coefficient of x^1 : h(0)=0 */
} step_element;



/*description of a function h on 'size' intervals. On each
  interval h is described with data, a step_element
*/

typedef struct
{
  int                   size;/*!< number of intervals */
  step_element  *data;/*!< data[i] contains the
                        description of the polynomial
                        function on the ith interval*/
} step_fun;
```

```
/*@}*/

/**
 * \ addtogroup Polynomial Step Functions
 */
/*@{*/
step_fun        *copy_sf(const step_fun         *sf);

step_fun                *init_constant_sf(int             size,
    const double          *x,
    const double          *y);

step_fun                *init_cont_linear_sf(int          size,
    const double       *x,
    const double       *y);

step_fun                *integrate_sf(const step_fun            *sf);

double                  compute_sf(const step_fun               *sf,
                                   double                x);

double                  inverse_sf(const step_fun               *sf,
                                   double                y);

void                    free_step_fun(step_fun                  **sf);
/*@}*/

/** Grid : contains 2 arrays of size 'size'. The first array
    contains 'data' and the second one contains 'delta': for i>=1
    delta(i)=data(i)-data(i-1), delta(0)=delta(1)
*/

/**
 * \ defgroup Grid
 */
/*@{*/
typedef struct
{
  int                   size;/*!< size of the arrays*/
  double                *data;/*!< array of datas*/
  double                *delta;/*!< array of data differences : delta(i)=data(i)
```

```
} grid;
/*@}*/

/**
 * \ addtogroup Grid
 */
/*@{*/
grid                    *create_grid(int  n);
grid                    *init_grid_cdo(int        n,
                                       const double     *x);
grid                    *init_hom_grid(double     x0,
                                       double     xn,
                                       double     delta);
grid                    *init_fine_grid(const grid      *gd_init,
                                        int       n);
void                    free_grid(grid                  *gd);
/*@}*/

#endif /* __STRUCTS_H__ */
```