

[Help](#)

```
#if defined(PremiaCurrentVersion) && PremiaCurrentVersion < (2009+2) //The "#els
#else

#include "
href../../common/math/wienerhopf_h_src.pdfwienerhopf.h"
#include "
href../../common/math/wienerhopf_rs_h_src.pdfwienerhopf_rs.h"
// model = 1 TSL
// model = 2 NIG
// model = 3 VGP
// model = 4 KOU

/*
 * A wrapper around pnl_real_ifft_inplace used by the other functions of this
 * file. The order of the storage is changed
 * if i is even then  $a(2i)+ I * a(2i+1)$  is the i-th
 * coefficients of the Fourier transform
 * if i is odd then  $a(N-2i)+ I * a(N-2i+1)$  is the i-th
 * coefficients of the Fourier transform
 */

void fft_real(PnlVect *a, int fft_size, int sign)
{
    int i, opposite;
    double last, second;

    switch (sign)
    {
        case 1 : /* backward */
            second = pnl_vect_get(a, 1);
            opposite = 1;
            for (i = 1 ; i < fft_size - 1 ; i++)
            {
                pnl_vect_set(a, i, opposite * pnl_vect_get(a, i + 1));
                opposite = - opposite;
            }
            pnl_vect_set(a , fft_size - 1, second);

            pnl_real_ifft_inplace(a->array, fft_size);
```

```

        break;
    case -1 : /* forward */
        pnl_real_fft_inplace(a->array, fft_size);
        last = pnl_vect_get(a, fft_size - 1);
        opposite = -1;
        for (i = fft_size - 1 ; i > 1 ; i--)
        {
            pnl_vect_set(a, i, opposite * pnl_vect_get(a, i - 1));
            opposite = - opposite;
        }
        pnl_vect_set(a , 1, last);
        break;
    }
}

```

```

//=====
static int findcoef(int model, double mu, double sigma, double lm1, double lp1,
                    double num, double nup,
                    double cnum, double cnup, double q, double r1,
                    double T, double h, long int kmax,
                    double er, long int Nt,
                    PnlVect *al1)

{
    PnlVect *bl1;
    long int k;
    long int i;
    double mod;
    PnlVect *alin1;
    double xi, xip, xim, anp, anm, sxi, nup1, num1;
    double lpm1;

    double sg2;
    double cpl;    // !!!!!
    double cml;

    /*Memory allocation for space grid*/

    bl1 = pnl_vect_create(2 * kmax + 1);

```

```

////////// this part depends on model
if (model == 1/*TSL*/)
{
    lpm1 = q + pow(lp1, nup) * cnup + pow(-lm1, num) * cnum;

    nup1 = nup / 2;
    num1 = num / 2;
    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = pow(xi * xi + lp1 * lp1, nup1);
    xim = pow(xi * xi + lm1 * lm1, num1);
    anp = nup * atan(xi / lp1);
    anm = num * atan(xi / lm1);
    bl1->array[1] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm);
    bl1->array[2 * kmax] = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = pow(xi * xi + lp1 * lp1, nup1);
        xim = pow(xi * xi + lm1 * lm1, num1);
        anp = nup * atan(xi / lp1);
        anm = num * atan(xi / lm1);
        bl1->array[2 * i] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm);
        bl1->array[2 * i + 1] = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END TSL
if (model == 2/*NIG*/)
{
    lpm1 = q - sqrt(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;

```

```

anp = 0.5 * atan(xim / xip);
bl1->array[1] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
bl1->array[2 * kmax] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = 0.5 * atan(xim / xip);
    bl1->array[2 * i] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
    bl1->array[2 * i + 1] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
    i++;
    xi = xi + sxi;
}
while (i < kmax);
} // END NIG
if (model == 3/*VGP*/)
{
    lpm1 = q - log(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = atan(xim / xip);
    bl1->array[1] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
    bl1->array[2 * kmax] = cnup * anp - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;
        xim = -(lp1 + lm1) * xi;
        anp = atan(xim / xip);
        bl1->array[2 * i] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
        bl1->array[2 * i + 1] = cnup * anp - mu * xi;
    }
}

```

```

        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END VGP
if (model == 4/*KOU*/)
{
    // nup==sigma
    sg2 = sigma * sigma / 2;
    cpl = cnup * lp1; // !!!!!!!
    cml = cnum * lm1;

    //lpm1=q+pow(lp1,nup)*cnup+pow(-lm1,num)*cnum;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi + lp1 * lp1;
    xim = xi * xi + lm1 * lm1;
    bl1->array[1] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
    bl1->array[2 * kmax] = xi * (cpl / xip + cml / xim) - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi + lp1 * lp1;
        xim = xi * xi + lm1 * lm1;
        bl1->array[2 * i] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
        bl1->array[2 * i + 1] = xi * (cpl / xip + cml / xim) - mu * xi;
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);

    } // END KOU
    //////////////////////////////////////

    alin1 = pnl_vect_create(2 * kmax);

    alin1->array[0] = q / bl1->array[0];

```

```

mod = bl1->array[2 * kmax] * bl1->array[2 * kmax] + bl1->array[1] * bl1->array[1];
alin1->array[1] = q * bl1->array[1] / mod;
//alin1->array[1]=q/bl1->array[1];

i = 1;
do
{
    mod = bl1->array[2 * i + 1] * bl1->array[2 * i + 1] + bl1->array[2 * i] *
    alin1->array[2 * i + 1] = -q * bl1->array[2 * i + 1] / mod;
    alin1->array[2 * i] = q * bl1->array[2 * i] / mod;
    i++;
}
while (i < kmax);

k = 0;
while (k < 2 * kmax)
{
    k++;
    al1->array[k] = alin1->array[k - 1];
}
pnl_vect_free(&alin1);
pnl_vect_free(&bl1);
return 1;
}

```

```

int findcoefnew(int model, double mu, double sigma, double lm1, double lp1,
                double num, double nup,
                double cnum, double cnup, double q, double r1,
                double T, double h, long int kmax,
                double er, long int Nt,
                PnlVect *al1)

{
    long int Nx;
    PnlVect *bl1;
    PnlVect *alin1;
    double sg2;
    double cpl;
    double cml;

```

```

long int k;
long int i;
double mod;

double xi, xip, xim, anp, anm, sxi, nup1, num1;
long int Nmax = 2 * kmax;
double lpm1;

Nx = Nmax; /*number of space points*/

/*Memory allocation for space grid*/

bl1 = pnl_vect_create(Nx + 1);
alin1 = pnl_vect_create(Nx);

////////////////////// this part depends on the model
if (model == 1/*TSL*/)
{
    lpm1 = q + pow(lp1, nup) * cnup + pow(-lm1, num) * cnum + fabs(mu) / h;

    nup1 = nup / 2.0;
    num1 = num / 2.0;
    LET(bl1, 0) = q;
    xi = -M_PI / h;
    xip = pow(xi * xi + lp1 * lp1, nup1);
    xim = pow(xi * xi + lm1 * lm1, num1);
    anp = nup * atan(xi / lp1);
    anm = num * atan(xi / lm1);
    LET(bl1, 1) = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm) + fabs(mu);
    LET(bl1, 2 * kmax) = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = pow(xi * xi + lp1 * lp1, nup1);
        xim = pow(xi * xi + lm1 * lm1, num1);
        anp = nup * atan(xi / lp1);

```

```

        anm = num * atan(xi / lm1);
        LET(b11, 2 * i) = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm)
        LET(b11, 2 * i + 1) = -cnup * xip * sin(anp) - cnum * xim * sin(anm) -
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END TSL
if (model == 2/*NIG*/)
{
    lpm1 = q - sqrt(-lp1 * lm1) * cnup;

    LET(b11, 0) = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = 0.5 * atan(xim / xip);
    LET(b11, 1) = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
    LET(b11, 2 * kmax) = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;
        xim = -(lp1 + lm1) * xi;
        anp = 0.5 * atan(xim / xip);
        LET(b11, 2 * i) = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos
        LET(b11, 2 * i + 1) = cnup * pow(xip * xip + xim * xim, 0.25) * sin(an
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END NIG
if (model == 3/*VGP*/)
{
    lpm1 = q - log(-lp1 * lm1) * cnup;

    LET(b11, 0) = q;
    xi = -M_PI / h;

```



```

xip = xi * xi - lp1 * lm1;
xim = -(lp1 + lm1) * xi;
anp = atan(xim / xip);
LET(b11, 1) = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
LET(b11, 2 * kmax) = cnup * anp - mu * xi;
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = atan(xim / xip);
    LET(b11, 2 * i) = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
    LET(b11, 2 * i + 1) = cnup * anp - mu * xi;
    i++;
    xi = xi + sxi;
}
while (i < kmax);
} // END VGP
if (model == 4/*KOU*/)
{
    sg2 = sigma * sigma / 2;
    cpl = cnup * lp1;
    cml = cnum * lm1;

    LET(b11, 0) = q;
    xi = -M_PI / h;
    xip = xi * xi + lp1 * lp1;
    xim = xi * xi + lm1 * lm1;
    LET(b11, 1) = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
    LET(b11, 2 * kmax) = xi * (cpl / xip + cml / xim) - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi + lp1 * lp1;
        xim = xi * xi + lm1 * lm1;

```

```

        LET(bl1, 2 * i) = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
        LET(bl1, 2 * i + 1) = xi * (cpl / xip + cml / xim) - mu * xi;
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);

} // END KOU

if (model == 6/*BS or Heston*/)
{
    // num==var
    double sg2 = sigma / 2;
    if (sg2 > 0.00001)
    {
        LET(bl1, 0) = q;
        xi = -M_PI / h;
        xip = xi * xi;
        LET(bl1, 1) = q + sg2 * xip;
        LET(bl1, 2 * kmax) = -mu * xi;
        sxi = xi / kmax;
        xi = sxi;

        i = 1;
        do
        {
            xip = xi * xi;
            LET(bl1, 2 * i) = q + sg2 * xip;
            LET(bl1, 2 * i + 1) = -mu * xi;
            i++;
            xi = xi + sxi;
        }
        while (i < kmax);
    }
    else
    {
        lpm1 = q + fabs(mu) / h;
        LET(bl1, 0) = q;
        xi = -M_PI / h;
        xip = xi * xi;
        LET(bl1, 1) = lpm1 + sg2 * xip + fabs(mu) / h;
        LET(bl1, 2 * kmax) = 0;
    }
}

```

```

        sxi = xi / kmax;
        xi = sxi;

        i = 1;
        do
        {
            xip = xi * xi;
            LET(bl1, 2 * i) = lpm1 + sg2 * xip - fabs(mu) * cos(xi * h) / h;
            LET(bl1, 2 * i + 1) = -mu * sin(xi * h) / h;
            i++;
            xi = xi + sxi;
        }
        while (i < kmax);
    }
} //END Heston
////////////////////////////////////

LET(alin1, 0) = q / GET(bl1, 0);
mod = GET(bl1, 2 * kmax) * GET(bl1, 2 * kmax) + GET(bl1, 1) * GET(bl1, 1);
LET(alin1, 1) = q * GET(bl1, 1) / mod;

i = 1;
do
{
    mod = GET(bl1, 2 * i + 1) * GET(bl1, 2 * i + 1) + GET(bl1, 2 * i) * GET(bl1, 2 * i);
    LET(alin1, 2 * i + 1) = -q * GET(bl1, 2 * i + 1) / mod;
    LET(alin1, 2 * i) = q * GET(bl1, 2 * i) / mod;
    i++;
}
while (i < kmax);

k = 0;
while (k < 2 * kmax)
{
    k++;
    LET(al1, k) = GET(alin1, k - 1);
}
pnl_vect_free(&alin1);
pnl_vect_free(&bl1);
return 1;

```

```

}
int findcoef_mc(int model, double mu, double sigma, double lm1, double lp1,
double num, double nup,
double cnum, double cnup, double q, double r1,
double T, double h, long int kmax,
double er, long int Nt,
PnlVect * al1)

{
PnlVect *bl1;
long int k;
long int i;
double mod;
PnlVect *alin1;
double xi, xip, xim, anp, anm, sxi, nup1, num1;
double lpm1;

double sg2;
double cpl;      // !!!!!
double cml;

//Memory allocation for space grid//

bl1 = pnl_vect_create(2 * kmax + 1);

////////////////////// this part depends on model
if (model == 1)//TSL
{

lpm1 = q + pow(lp1, nup)*cnup + pow(-lm1, num)*cnum;

nup1 = nup / 2;
num1 = num / 2;
bl1->array[0] = q;
xi = -M_PI / h;
xip = pow(xi*xi + lp1*lp1, nup1);
xim = pow(xi*xi + lm1*lm1, num1);
anp = nup*atan(xi / lp1);
anm = num*atan(xi / lm1);
bl1->array[1] = lpm1 - cnup*xip*cos(anp) - cnum*xim*cos(anm);
bl1->array[2 * kmax] = -cnup*xip*sin(anp) - cnum*xim*sin(anm) - mu*xi;;

```

```

sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
xip = pow(xi*xi + lp1*lp1, nup1);
xim = pow(xi*xi + lm1*lm1, num1);
anp = nup*atan(xi / lp1);
anm = num*atan(xi / lm1);
bl1->array[2 * i] = lpm1 - cnup*xip*cos(anp) - cnum*xim*cos(anm);
bl1->array[2 * i + 1] = -cnup*xip*sin(anp) - cnum*xim*sin(anm) - mu*xi;;
i++;
xi = xi + sxi;
} while (i<kmax);
} // END TSL
if (model == 2) // NIG //
{
lpm1 = q - sqrt(-lp1*lm1)*cnup;

bl1->array[0] = q;
xi = -M_PI / h;
xip = xi*xi - lp1*lm1;
xim = -(lp1 + lm1)*xi;
anp = 0.5*atan(xim / xip);
bl1->array[1] = lpm1 + cnum*pow(xip*xip + xim*xim, 0.25)*cos(anp);
bl1->array[2 * kmax] = cnup*pow(xip*xip + xim*xim, 0.25)*sin(anp);
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
xip = xi*xi - lp1*lm1;
xim = -(lp1 + lm1)*xi;
anp = 0.5*atan(xim / xip);
bl1->array[2 * i] = lpm1 + cnum*pow(xip*xip + xim*xim, 0.25)*cos(anp);
bl1->array[2 * i + 1] = cnup*pow(xip*xip + xim*xim, 0.25)*sin(anp);
i++;
xi = xi + sxi;
} while (i<kmax);

```

```

} // END NIG
if (model == 3) //VGP//
{
lpm1 = q - log(-lp1*lm1)*cnup;

bl1->array[0] = q;
xi = -M_PI / h;
xip = xi*xi - lp1*lm1;
xim = -(lp1 + lm1)*xi;
anp = atan(xim / xip);
bl1->array[1] = lpm1 + cnup*log(xip*xip + xim*xim) / 2;
bl1->array[2 * kmax] = cnup*anp - mu*xi;
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
xip = xi*xi - lp1*lm1;
xim = -(lp1 + lm1)*xi;
anp = atan(xim / xip);
bl1->array[2 * i] = lpm1 + cnup*log(xip*xip + xim*xim) / 2;
bl1->array[2 * i + 1] = cnup*anp - mu*xi;
i++;
xi = xi + sxi;
} while (i < kmax);
} // END VGP
if (model == 4) //KOU//
{
// nup==sigma
sg2 = sigma*sigma / 2;
cpl = cnup*lp1; // !!!!!
cml = cnum*lm1;

//lpm1=q+pow(lp1,nup)*cnup+pow(-lm1,num)*cnum;

bl1->array[0] = q;
xi = -M_PI / h;
xip = xi*xi + lp1*lp1;
xim = xi*xi + lm1*lm1;
bl1->array[1] = q + (sg2 + cnup / xip + cnum / xim)*xi*xi;

```

```

bl1->array[2 * kmax] = xi*(cpl / xip + cml / xim) - mu*xi;
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
xip = xi*xi + lp1*lp1;
xim = xi*xi + lm1*lm1;
bl1->array[2 * i] = q + (sg2 + cnup / xip + cnum / xim)*xi*xi;
bl1->array[2 * i + 1] = xi*(cpl / xip + cml / xim) - mu*xi;
i++;
xi = xi + sxi;
} while (i<kmax);

}//  END KOU
////////////////////////////////////

alin1 = pnl_vect_create(2 * kmax);

alin1->array[0] = q / bl1->array[0];
mod = bl1->array[2 * kmax] * bl1->array[2 * kmax] + bl1->array[1] * bl1->array[1];
alin1->array[1] = q*bl1->array[1] / mod;
//alin1->array[1]=q/bl1->array[1];

i = 1;
do
{
mod = bl1->array[2 * i + 1] * bl1->array[2 * i + 1] + bl1->array[2 * i] * bl1->array[2 * i];
alin1->array[2 * i + 1] = -q*bl1->array[2 * i + 1] / mod;
alin1->array[2 * i] = q*bl1->array[2 * i] / mod;
i++;
} while (i<kmax);

k = 0;
while (k<2 * kmax)
{
k++;
al1->array[k] = alin1->array[k - 1];
}

```

```

pnl_vect_free(&alin1);
pnl_vect_free(&bl1);
return 1;
}

//=====
static int findcoef_sw(int model, double mu, double sigma, double lm1, double lp1,
double num, double nup,
double cnum, double cnup, double q, double r1,
double T, double h, long int kmax,
double del, long int Nt,
PnlVect *al1, PnlVect *bl1)

{
//double *bl1;
long int k;
long int i;
double mod;
PnlVect *alin1;
double xi, xip, xim, anp, anm, sxi, nup1, num1, del1;
double lpm1;
double dt1;

/*Memory allocation for space grid*/

// bl1=new double[2*kmax+1];

dt1 = Nt / T;
del1 = 1 / dt1 - del;
// cout<<del1<<" " <<dt1<<endl;
////////// this part depends on model
if (model == 1/*TSL*/)
{
lpm1 = q + pow(lp1, nup) * cnup + pow(-lm1, num) * cnum + fabs(mu) / h;

nup1 = nup / 2.0;
num1 = num / 2.0;
bl1->array[0] = q;
xi = -M_PI / h;

```



```

xip = pow(xi * xi + lp1 * lp1, nup1);
xim = pow(xi * xi + lm1 * lm1, num1);
anp = nup * atan(xi / lp1);
anm = num * atan(xi / lm1);
bl1->array[1] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm) + fab;
bl1->array[2 * kmax] = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
    xip = pow(xi * xi + lp1 * lp1, nup1);
    xim = pow(xi * xi + lm1 * lm1, num1);
    anp = nup * atan(xi / lp1);
    anm = num * atan(xi / lm1);
    bl1->array[2 * i] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm);
    bl1->array[2 * i + 1] = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
    i++;
    xi = xi + sxi;
}
while (i < kmax);
} // END TSL
if (model == 2/*NIG*/)
{
    lpm1 = q - sqrt(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = 0.5 * atan(xim / xip);
    bl1->array[1] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
    bl1->array[2 * kmax] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;

```

```

        xim = -(lp1 + lm1) * xi;
        anp = 0.5 * atan(xim / xip);
        bl1->array[2 * i] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * c
        bl1->array[2 * i + 1] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END NIG
if (model == 3/*VGP*/)
{
    lpm1 = q - log(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = atan(xim / xip);
    bl1->array[1] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
    bl1->array[2 * kmax] = cnup * anp - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;
        xim = -(lp1 + lm1) * xi;
        anp = atan(xim / xip);
        bl1->array[2 * i] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
        bl1->array[2 * i + 1] = cnup * anp - mu * xi;
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END VGP
if (model == 4/*KOU*/)
{
    // nup==sigma
    double sg2 = sigma * sigma / 2;
    double cpl = cnup * lp1; // !!!!!

```

```

double cml = cnum * lm1;

//lpm1=q+pow(lp1,nup)*cnup+pow(-lm1,num)*cnum;

bl1->array[0] = q;
xi = -M_PI / h;
xip = xi * xi + lp1 * lp1;
xim = xi * xi + lm1 * lm1;
bl1->array[1] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
bl1->array[2 * kmax] = xi * (cpl / xip + cml / xim) - mu * xi;
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
    xip = xi * xi + lp1 * lp1;
    xim = xi * xi + lm1 * lm1;
    bl1->array[2 * i] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
    bl1->array[2 * i + 1] = xi * (cpl / xip + cml / xim) - mu * xi;
    i++;
    xi = xi + sxi;
}
while (i < kmax);

} // END KOU

if (model == 5/*Merton*/) //nup=delta; cnum=lambda;cnup=gam0;
{
    // nup==sigma
    double sg2 = sigma * sigma / 2;
    double del2 = nup * nup / 2; // !!!!!
    double gam1 = cnup;

    //lpm1=q+pow(lp1,nup)*cnup+pow(-lm1,num)*cnum;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi;
    bl1->array[1] = q + sg2 * xip + cnum * (1 - exp(-del2 * xip) * cos(gam1 *
    bl1->array[2 * kmax] = -cnum * exp(-del2 * xip) * sin(gam1 * xi) - mu * xi
    sxi = xi / kmax;

```

```

xi = sxi;

i = 1;
do
{
    xip = xi * xi;
    bl1->array[2 * i] = q + sg2 * xip + cnum * (1 - exp(-del2 * xip) * cos
    bl1->array[2 * i + 1] = -cnum * exp(-del2 * xip) * sin(gam1 * xi) - mu
    i++;
    xi = xi + sxi;
}
while (i < kmax);

} // END MERTON
////////////////////////////////////

alin1 = pnl_vect_create(2 * kmax);

alin1->array[0] = q / bl1->array[0];
bl1->array[0] = exp(del1 * (bl1->array[0] - dt1));
mod = bl1->array[2 * kmax] * bl1->array[2 * kmax] + bl1->array[1] * bl1->array
alin1->array[1] = q * bl1->array[1] / mod;
bl1->array[1] = exp(del1 * (bl1->array[1] - dt1));
//alin1->array[1]=q/bl1->array[1];
i = 1;
do
{
    mod = bl1->array[2 * i + 1] * bl1->array[2 * i + 1] + bl1->array[2 * i] *
    alin1->array[2 * i + 1] = -q * bl1->array[2 * i + 1] / mod;
    alin1->array[2 * i] = q * bl1->array[2 * i] / mod;
    bl1->array[2 * i] = exp(del1 * (bl1->array[2 * i] - dt1));
    mod = del1 * bl1->array[2 * i + 1];
    bl1->array[2 * i + 1] = bl1->array[2 * i] * sin(mod);
    bl1->array[2 * i] = bl1->array[2 * i] * cos(mod);
    i++;
}
while (i < kmax);

k = 0;
while (k < 2 * kmax)
{

```

```

        k++;
        al1->array[k] = alin1->array[k - 1];
    }
    pnl_vect_free(&alin1);
    return 1;
}
//-----findfactor-----
int findfactor(double np, double nm, double h, long int kmax, double lp1, double
{
    PnlVect *tb1, *tbp1, *tbm1, *ltp1, *ltm1;

    long int i;

    double xi, xip, xim, anp, anm, sxi, abp, abm, nup1, num1;
    double t1, t2;
    double angle;
    double mod;

    long int Nmax = 2 * kmax;

    tbp1 = pnl_vect_create(Nmax + 2);
    ltp1 = pnl_vect_create(Nmax + 2);
    ltm1 = pnl_vect_create(Nmax + 2);
    tb1 = pnl_vect_create(Nmax + 2);
    tbm1 = pnl_vect_create(Nmax + 2);

    nup1 = 0.;
    num1 = 0.;

    if (np == nm)
    {
        nup1 = np / 2.0;
        num1 = nm / 2.0;
    }
    if (np > nm)
    {
        nup1 = np;
        num1 = 0.0;
    }
    if (np < nm)
    {

```

```

        nup1 = 0.0;
        num1 = nm;
    }

    abp = pow(lp1, nup1);
    abm = pow(-lm1, num1);

    LET(ltp1, 0) = 1;
    LET(ltm1, 0) = 1;
    xi = -M_PI / h;

    xip = pow(xi * xi + lp1 * lp1, nup1 / 2.0) / abp;
    xim = pow(xi * xi + lm1 * lm1, num1 / 2.0) / abm;
    anp = nup1 * atan(xi / lp1);
    anm = num1 * atan(xi / lm1);
    LET(ltp1, 1) = xip * cos(anp);
    LET(ltm1, 1) = xim * cos(anm);
    LET(ltp1, 2 * kmax) = xip * sin(anp);
    LET(ltm1, 2 * kmax) = xim * sin(anm);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = pow(xi * xi + lp1 * lp1, nup1 / 2.0) / abp;
        xim = pow(xi * xi + lm1 * lm1, num1 / 2.0) / abm;
        anp = nup1 * atan(xi / lp1);
        anm = num1 * atan(xi / lm1);
        LET(ltp1, 2 * i) = xip * cos(anp);
        LET(ltp1, 2 * i + 1) = xip * sin(anp);
        LET(ltm1, 2 * i) = xim * cos(anm);
        LET(ltm1, 2 * i + 1) = xim * sin(anm);
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);

    LET(alin1, 1) = GET(alin1, 1) * (GET(ltp1, 1) * GET(ltm1, 1) - GET(ltp1, 2 * k
for (i = 1; i <= kmax - 1; i++)
{

```

```

    t1 = GET(alin1, 2 * i);
    t2 = GET(alin1, 2 * i + 1);
    LET(alin1, 2 * i) = t1 * GET(ltm1, 2 * i) - t2 * GET(ltm1, 2 * i + 1);
    LET(alin1, 2 * i + 1) = t2 * GET(ltm1, 2 * i) + t1 * GET(ltm1, 2 * i + 1);
}
for (i = 1; i <= kmax - 1; i++)
{
    t1 = GET(alin1, 2 * i);
    t2 = GET(alin1, 2 * i + 1);
    LET(alin1, 2 * i) = t1 * GET(ltp1, 2 * i) - t2 * GET(ltp1, 2 * i + 1);
    LET(alin1, 2 * i + 1) = t2 * GET(ltp1, 2 * i) + t1 * GET(ltp1, 2 * i + 1);
}

LET(ltp1, 0) = 1 / GET(ltp1, 0);
LET(ltm1, 0) = 1 / GET(ltm1, 0);
LET(ltp1, 1) = GET(ltp1, 1) / (GET(ltp1, 1) * GET(ltp1, 1) + GET(ltp1, 2 * kma
LET(ltm1, 1) = GET(ltm1, 1) / (GET(ltm1, 1) * GET(ltm1, 1) + GET(ltm1, 2 * kma

i = 1;
do
{
    mod = GET(ltp1, 2 * i + 1) * GET(ltp1, 2 * i + 1) + GET(ltp1, 2 * i) * GET
    LET(ltp1, 2 * i + 1) = -GET(ltp1, 2 * i + 1) / mod;
    LET(ltp1, 2 * i) = GET(ltp1, 2 * i) / mod;

    mod = GET(ltm1, 2 * i + 1) * GET(ltm1, 2 * i + 1) + GET(ltm1, 2 * i) * GET
    LET(ltm1, 2 * i + 1) = -GET(ltm1, 2 * i + 1) / mod;
    LET(ltm1, 2 * i) = GET(ltm1, 2 * i) / mod;
    i++;
}
while (i < kmax);

LET(tb1, 0) = log(GET(alin1, 0));
LET(tb1, 1) = log(GET(alin1, 1));

i = 1;
do
{
    mod = GET(alin1, 2 * i + 1) * GET(alin1, 2 * i + 1) + GET(alin1, 2 * i) *
    LET(tb1, 2 * i) = 0.5 * log(mod);
    if (GET(alin1, 2 * i) == 0)

```

```

    {
        if (GET(alin1, 2 * i + 1) > 0)
        {
            LET(tb1, 2 * i + 1) = M_PI / 2.0;
        }
        else
        {
            LET(tb1, 2 * i + 1) = -M_PI / 2.0;
        }
    }
else
{
    angle = atan(GET(alin1, 2 * i + 1) / GET(alin1, 2 * i));
    if (GET(alin1, 2 * i) > 0)
    {
        LET(tb1, 2 * i + 1) = angle;
    }
    if (GET(alin1, 2 * i) < 0)
    {
        if (GET(alin1, 2 * i + 1) < 0)
        {
            LET(tb1, 2 * i + 1) = angle - M_PI;
        }
        else
        {
            LET(tb1, 2 * i + 1) = angle + M_PI;
        }
    }
}
    i++;
}
while (i < kmax);

fft_real(tb1, 2 * kmax, 1);

i = 1;
LET(tbp1, 0) = 0;
LET(tbm1, 0) = 0;
do
{

```



```

        LET(tbp1, 0) = GET(tbp1, 0) - GET(tb1, i);
        LET(tbp1, i) = GET(tb1, i);
        LET(tbm1, i) = 0;
        i++;
    }
while (i < kmax);
do
{
    LET(tbm1, i) = GET(tb1, i);
    LET(tbp1, i) = 0;
    LET(tbm1, 0) = GET(tbm1, 0) - GET(tb1, i);
    i++;
}
while (i < 2 * kmax);

fft_real(tbp1, 2 * kmax, -1);
fft_real(tbm1, 2 * kmax, -1);

LET(tp1, 0) = exp(GET(tbp1, 0));
LET(tp1, 1) = exp(GET(tbp1, 1));
LET(tm1, 0) = exp(GET(tbm1, 0));
LET(tm1, 1) = exp(GET(tbm1, 1));

i = 1;
do
{
    mod = exp(GET(tbp1, 2 * i));
    LET(tp1, 2 * i) = mod * cos(GET(tbp1, 2 * i + 1));
    LET(tp1, 2 * i + 1) = mod * sin(GET(tbp1, 2 * i + 1));
    mod = exp(GET(tbm1, 2 * i));
    LET(tm1, 2 * i) = mod * cos(GET(tbm1, 2 * i + 1));
    LET(tm1, 2 * i + 1) = mod * sin(GET(tbm1, 2 * i + 1));
    i++;
}
while (i < kmax);

LET(tp1, 0) = GET(tp1, 0) * GET(ltp1, 0);
LET(tp1, 1) = GET(tp1, 1) * GET(ltp1, 1);

LET(tm1, 0) = GET(tm1, 0) * GET(ltm1, 0);
LET(tm1, 1) = GET(tm1, 1) * GET(ltm1, 1);

```

```

for (i = 1; i <= kmax - 1; i++)
{
    t1 = GET(tm1, 2 * i);
    t2 = GET(tm1, 2 * i + 1);
    LET(tm1, 2 * i) = t1 * GET(ltm1, 2 * i) - t2 * GET(ltm1, 2 * i + 1);
    LET(tm1, 2 * i + 1) = t2 * GET(ltm1, 2 * i) + t1 * GET(ltm1, 2 * i + 1);
}
for (i = 1; i <= kmax - 1; i++)
{
    t1 = GET(tp1, 2 * i);
    t2 = GET(tp1, 2 * i + 1);
    LET(tp1, 2 * i) = t1 * GET(ltp1, 2 * i) - t2 * GET(ltp1, 2 * i + 1);
    LET(tp1, 2 * i + 1) = t2 * GET(ltp1, 2 * i) + t1 * GET(ltp1, 2 * i + 1);
}

pnl_vect_free(&tbp1);
pnl_vect_free(&ltp1);
pnl_vect_free(&ltm1);
pnl_vect_free(&tb1);
pnl_vect_free(&tbm1);

return 1;
} //end findfactor

/*//////////////////////// BARRIER AND DIGITAL //////////////////////////*/

int fastwienerhopf(int model, double mu, double qu, double om, int am, int upord,
    double num, double nup, double cnum, double cnup,
    double r, double divid,
    double T, double h, double Strike1,
    double bar, double rebate,
    double er, long int step,
    double *ptprice, double *ptdelta)
{
    PnlVect *t, *y, *v1, *vv1, *tp1, *tm1,
        *tb1, *tbp1, *tbm1, *ltp1, *ltm1, *alin1, *eom, *reb, *switcharrow, *a;
    long int N1 = 0, Nx, kmax, j, L;

    double pp;

```

```

double xi, xip, xim, anp, anm, sxi, nup1 = 1., num1 = 1., abp, abm;
double t1, t2;
double angle;
double a2_1 = 0.;
double mut;
double mod;
long int i;
long int k;
long int Nmax, N01;
double dt;

double q;
double mu1 = 0., str, kx;
double Sl, Sm, Sr;
double pricel, pricem, pricer;
double A, B, C;
double sigma;

if (upordown == 0)
{
    if (Spot <= bar)
    {
        *ptprice = rebate;
        *ptdelta = 0.;
        return OK;
    }
    if (Spot >= 0.8 * bar * exp(er * log(2.)))
    {
        *ptprice = 0.;
        *ptdelta = 0.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}
else
{
    if (Spot >= bar)
    {
        *ptprice = rebate;
        *ptdelta = 0.;
        return OK;
    }
}

```

```

    }
    if (Spot <= bar * exp(-er * log(2.)) * 1.2)
    {
        *ptprice = 0.;
        *ptdelta = 0.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}

str = log(Strike1 / bar);

k = 64;

kx = er * log(2) / h;
while (k < kx)
{
    k = k * 2;
}
kmax = k;

N1 = step;
Nmax = 2 * kmax;
N01 = kmax;          //   !!!kmax

//Memory allocation for space grid
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points
v1 = pnl_vect_create_from_zero(Nmax + 1); //prices at previous time step
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
tp1 = pnl_vect_create_from_zero(2 * kmax + 2);
alin1 = pnl_vect_create_from_zero(2 * kmax + 2);
tbp1 = pnl_vect_create_from_zero(2 * kmax + 2);
ltp1 = pnl_vect_create_from_zero(2 * kmax + 2);
ltm1 = pnl_vect_create_from_zero(2 * kmax + 2);
tb1 = pnl_vect_create_from_zero(2 * kmax + 2);
tbm1 = pnl_vect_create_from_zero(2 * kmax + 2);
tm1 = pnl_vect_create_from_zero(2 * kmax + 2);
al1 = pnl_vect_create_from_zero(2 * kmax + 2);
eom = pnl_vect_create_from_zero(Nmax + 1);
reb = pnl_vect_create_from_zero(Nmax + 1);
t = pnl_vect_create_from_zero(N1 + 2); //time points

```

```

lp1 += om;
lm1 += om;

/*Time step*/
dt = T / N1;
t->array[1] = 0;

q = qu + 1 / dt;

//===== compute coefficients
if (model == 1)
{
    mu1 = mu;
    sigma = 0.;
}
if (model == 2)
{
    mu1 = mu;
    sigma = 0.;
}
if (model == 3)
{
    mu1 = 0.0;
    sigma = 0.;
    if ((mu > 0.0) && (mu < 0.1))
    {
        mu1 = mu - 0.1;
    }
    if ((mu <= 0.0) && (mu > -0.1))
    {
        mu1 = mu + 0.1;
    }
    q += mu1 * om;
}
if (model == 4) /*KOU*/
{
    mu1 = 0.0; //mu

    sigma = nup;
    mu += sigma * sigma * om;
}

```

```

        nup = num;
        cnum *= (lm1 - om) / lm1;
        cnup *= (lp1 - om) / lp1;
    }
    findcoef(model, mu - mu1, sigma, lm1, lp1, num, nup, cnum, cnup, q, r, T, h, k
//=====
    a2_1 = q * dt;

    Nx = Nmax; /*number of space points*/
    i = 0;
    do
    {
        alin1->array[i] = al1->array[i + 1];
        i++;
    }
    while (i < 2 * kmax);

//if(model==1){
    if (nup == num)
    {
        nup1 = nup / 2.0;
        num1 = num / 2.0;
    }
    if (nup > num)
    {
        nup1 = nup; //
        num1 = 0.0;
    }
    if (nup < num)
    {
        nup1 = 0.0; //
        num1 = num;
    }
    abp = pow(lp1, nup1);
    abm = pow(-lm1, num1);

    ltp1->array[0] = 1;
    ltm1->array[0] = 1;
    xi = -M_PI / h;

    xip = pow(xi * xi + lp1 * lp1, nup1 / 2) / abp;

```

```

xim = pow(xi * xi + lm1 * lm1, num1 / 2) / abm;
anp = nup1 * atan(xi / lp1);
anm = num1 * atan(xi / lm1);
ltp1->array[1] = xip * cos(anp);
ltm1->array[1] = xim * cos(anm);
ltp1->array[2 * kmax] = xip * sin(anp);
ltm1->array[2 * kmax] = xim * sin(anm);
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
    xip = pow(xi * xi + lp1 * lp1, nup1 / 2) / abp;
    xim = pow(xi * xi + lm1 * lm1, num1 / 2) / abm;
    anp = nup1 * atan(xi / lp1);
    anm = num1 * atan(xi / lm1);
    ltp1->array[2 * i] = xip * cos(anp);
    ltp1->array[2 * i + 1] = xip * sin(anp);
    ltm1->array[2 * i] = xim * cos(anm);
    ltm1->array[2 * i + 1] = xim * sin(anm);
    i++;
    xi = xi + sxi;
}
while (i < kmax);

alin1->array[1] = alin1->array[1] * (ltp1->array[1] * ltm1->array[1] - ltp1->a
for (i = 1; i <= kmax - 1; i++)
{
    t1 = alin1->array[2 * i];
    t2 = alin1->array[2 * i + 1];
    alin1->array[2 * i] = t1 * ltm1->array[2 * i] - t2 * ltm1->array[2 * i + 1]
    alin1->array[2 * i + 1] = t2 * ltm1->array[2 * i] + t1 * ltm1->array[2 * i
}
for (i = 1; i <= kmax - 1; i++)
{
    t1 = alin1->array[2 * i];
    t2 = alin1->array[2 * i + 1];
    alin1->array[2 * i] = t1 * ltp1->array[2 * i] - t2 * ltp1->array[2 * i + 1]
    alin1->array[2 * i + 1] = t2 * ltp1->array[2 * i] + t1 * ltp1->array[2 * i
}

```

```

ltp1->array[0] = 1 / ltp1->array[0];
ltm1->array[0] = 1 / ltm1->array[0];
ltp1->array[1] = ltp1->array[1] / (ltp1->array[1] * ltp1->array[1] + ltp1->arr
ltm1->array[1] = ltm1->array[1] / (ltm1->array[1] * ltm1->array[1] + ltm1->arr
i = 1;
do
{
    mod = ltp1->array[2 * i + 1] * ltp1->array[2 * i + 1] + ltp1->array[2 * i]
    ltp1->array[2 * i + 1] = -ltp1->array[2 * i + 1] / mod;
    ltp1->array[2 * i] = ltp1->array[2 * i] / mod;

    mod = ltm1->array[2 * i + 1] * ltm1->array[2 * i + 1] + ltm1->array[2 * i]
    ltm1->array[2 * i + 1] = -ltm1->array[2 * i + 1] / mod;
    ltm1->array[2 * i] = ltm1->array[2 * i] / mod;
    i++;
}
while (i < kmax);

tb1->array[0] = log(alin1->array[0]);
tb1->array[1] = log(alin1->array[1]);
i = 1;
do
{
    mod = alin1->array[2 * i + 1] * alin1->array[2 * i + 1] + alin1->array[2 *
    tb1->array[2 * i] = 0.5 * log(mod);
    if (alin1->array[2 * i] == 0)
    {
        if (alin1->array[2 * i + 1] > 0)
        {
            tb1->array[2 * i + 1] = M_PI / 2.0;
        }
        else
        {
            tb1->array[2 * i + 1] = -M_PI / 2.0;
        }
    }
    else
    {
        angle = atan(alin1->array[2 * i + 1] / alin1->array[2 * i]);
        if (alin1->array[2 * i] > 0)

```



```

        {
            tb1->array[2 * i + 1] = angle;
        }
        if (alin1->array[2 * i] < 0)
        {
            if (alin1->array[2 * i + 1] < 0)
            {
                tb1->array[2 * i + 1] = angle - M_PI;
            }
            else
            {
                tb1->array[2 * i + 1] = angle + M_PI;
            }
        }
    }
    i++;
}
while (i < kmax);
i = 0;
do
{
    alin1->array[i] = al1->array[i + 1];
    i++;
}
while (i < 2 * kmax);
fft_real(tb1, 2 * kmax, 1);
i = 1;
tbp1->array[0] = 0;
tbm1->array[0] = 0;
do
{
    tbp1->array[0] = tbp1->array[0] - tb1->array[i];
    tbp1->array[i] = tb1->array[i];
    tbm1->array[i] = 0;
    i++;
}
while (i < kmax);
do
{
    tbm1->array[i] = tb1->array[i];
    tbp1->array[i] = 0;

```

```

        tbm1->array[0] = tbm1->array[0] - tb1->array[i];
        i++;
    }
    while (i < 2 * kmax);
    fft_real(tbp1, 2 * kmax, -1);
    fft_real(tbm1, 2 * kmax, -1);
    tp1->array[0] = exp(tbp1->array[0]);
    tp1->array[1] = exp(tbp1->array[1]);
    tm1->array[0] = exp(tbm1->array[0]);
    tm1->array[1] = exp(tbm1->array[1]);

    i = 1;
    do
    {
        mod = exp(tbp1->array[2 * i]);
        tp1->array[2 * i] = mod * cos(tbp1->array[2 * i + 1]);
        tp1->array[2 * i + 1] = mod * sin(tbp1->array[2 * i + 1]);
        mod = exp(tbm1->array[2 * i]);
        tm1->array[2 * i] = mod * cos(tbm1->array[2 * i + 1]);
        tm1->array[2 * i + 1] = mod * sin(tbm1->array[2 * i + 1]);
        i++;
    }
    while (i < kmax);

    tp1->array[0] = tp1->array[0] * ltp1->array[0];
    tp1->array[1] = tp1->array[1] * ltp1->array[1];

    tm1->array[0] = tm1->array[0] * ltm1->array[0];
    tm1->array[1] = tm1->array[1] * ltm1->array[1];

    for (i = 1; i <= kmax - 1; i++)
    {
        t1 = tm1->array[2 * i];
        t2 = tm1->array[2 * i + 1];
        tm1->array[2 * i] = t1 * ltm1->array[2 * i] - t2 * ltm1->array[2 * i + 1];
        tm1->array[2 * i + 1] = t2 * ltm1->array[2 * i] + t1 * ltm1->array[2 * i + 1];
    }
    for (i = 1; i <= kmax - 1; i++)
    {
        t1 = tp1->array[2 * i];
        t2 = tp1->array[2 * i + 1];

```

```

        tp1->array[2 * i] = t1 * ltp1->array[2 * i] - t2 * ltp1->array[2 * i + 1];
        tp1->array[2 * i + 1] = t2 * ltp1->array[2 * i] + t1 * ltp1->array[2 * i + 1];
    }

/*Put Pay-off functions*/
if (upordown == 0)
    for (j = 1; j <= kmax; j++)
    {
        y->array[j] = (j - N01 - 0.5) * h;
        vv1->array[j - 1] = 0;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
    }
else
    for (j = kmax; j <= Nmax; j++)
    {
        y->array[j] = (j - N01 + 0.5) * h;
        vv1->array[j - 1] = 0;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
    }

if (upordown == 0) // IF DOWN-OUT
{
    j = kmax + 1;

    if (ifCall == 2) /* DIGITAL */
    {
        do
        {
            y->array[j] = (j - N01 - 0.5) * h;
            eom->array[j] = exp(-om * y->array[j]);
            reb->array[j] = rebate * dt * r * eom->array[j];

            vv1->array[j - 1] = -rebate * eom->array[j];
            j++;
        }
        while (j <= Nmax);
    }
    else if (ifCall == 1) /* CALL */
    {

```

```

do
{
y->array[j] = (j - N01 - 0.5) * h;
eom->array[j] = exp(-om * y->array[j]);
reb->array[j] = rebate * dt * r * eom->array[j];
if (y->array[j] >= str)
{
vv1->array[j - 1] = (-Strike1 + bar * exp(y->array[j])) - rebat
}
else
{
vv1->array[j - 1] = -rebate * eom->array[j];
}
j++;
}
while (j <= Nmax);
}
else /* PUT */
{
do
{
y->array[j] = (j - N01 - 0.5) * h;
eom->array[j] = exp(-om * y->array[j]);
reb->array[j] = rebate * dt * r * eom->array[j];
if (y->array[j] <= str)
{
vv1->array[j - 1] = (Strike1 - bar * exp(y->array[j])) - rebate
}
else
{
vv1->array[j - 1] = -rebate * eom->array[j];
}
j++;
}
while (j <= Nmax);
}
} // END IF DOWN-OUT
else // IF UP-OUT
{
j = kmax - 1;

```

```

if (ifCall == 2) /* DIGITAL */
{
    do
    {
        y->array[j] = (j - N01 + 0.5) * h;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];

        {
            vv1->array[j - 1] = -rebate * eom->array[j];
        }
        j--;
    }
    while (j > 0);
}
else if (ifCall == 1) /* CALL */
{
    do
    {
        y->array[j] = (j - N01 + 0.5) * h;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
        if (y->array[j] >= str)
        {
            vv1->array[j - 1] = (-Strike1 + bar * exp(y->array[j])) - rebat
        }
        else
        {
            vv1->array[j - 1] = -rebate * eom->array[j];
        }
        j--;
    }
    while (j > 0);
}
else /* PUT */
{
    do
    {
        y->array[j] = (j - N01 + 0.5) * h;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];

```

```

        if (y->array[j] <= str)
        {
            vv1->array[j - 1] = (Strike1 - bar * exp(y->array[j]) - rebate
        }
        else
        {
            vv1->array[j - 1] = -rebate * eom->array[j];
        }
        j--;
    }
    while (j > 0);
}

} // END IF UP
//===== EXCHANGE tp AND tm ARRAYS FOR UP-OUT
if (upordown == 1)
{
    switcharrow = tp1;
    tp1 = tm1;
    tm1 = switcharrow;
}
//=====

for (i = 0; i < Nmax; i++)
{
    tp1->array[i] = tp1->array[i] / a2_1;
    alin1->array[i] = alin1->array[i] / a2_1;
}

fft_real(vv1, 2 * kmax, -1);

vv1->array[0] = vv1->array[0] * tm1->array[0];
vv1->array[1] = vv1->array[1] * tm1->array[1];

for (i = 1; i <= kmax - 1; i++)
{
    t1 = vv1->array[2 * i];
    t2 = vv1->array[2 * i + 1];
    vv1->array[2 * i] = t1 * tm1->array[2 * i] - t2 * tm1->array[2 * i + 1];
    vv1->array[2 * i + 1] = t2 * tm1->array[2 * i] + t1 * tm1->array[2 * i + 1];
}

```

```

fft_real(vv1, 2 * kmax, 1);

/*Main Loop on time grid*/

for (L = 2; L <= N1; L++)
{
    t->array[L] = t->array[L - 1] + dt;
    mut = t->array[L] * mu1;

    if (upordown == 0) // IF DOWN-OUT
    {
        i = 0;
        do
        {
            vv1->array[i] = 0;
            i++;
        }
        while (y->array[i + 1] <= mut);

        do
        {
            vv1->array[i] = vv1->array[i] - reb->array[i + 1];
            i++;
        }
        while (i < Nmax);
    }
    else //IF UP-OUT
    {
        i = Nmax; //-1;
        do
        {
            vv1->array[i] = 0;
            i--;
        }
        while (y->array[i + 1] >= mut);

        do
        {
            vv1->array[i] = vv1->array[i] - reb->array[i + 1];
            i--;
        }
    }
}

```

```

        while (i >= 0);
    }

    fft_real(vv1, 2 * kmax, -1);
    vv1->array[0] = vv1->array[0] * alin1->array[0];
    vv1->array[1] = vv1->array[1] * alin1->array[1];
    for (i = 1; i <= kmax - 1; i++)
    {
        t1 = vv1->array[2 * i];
        t2 = vv1->array[2 * i + 1];
        vv1->array[2 * i] = t1 * alin1->array[2 * i] - t2 * alin1->array[2 * i + 1];
        vv1->array[2 * i + 1] = t2 * alin1->array[2 * i] + t1 * alin1->array[2 * i + 1];
    }
    fft_real(vv1, 2 * kmax, 1);
} // END MAIN LOOP

t->array[N1 + 1] = t->array[N1] + dt;
mut = mul * t->array[N1 + 1];

if (upordown == 0) // IF DOWN-OUT                                !!
{
    i = 0;
    do
    {
        vv1->array[i] = 0;
        i++;
    }
    while (y->array[i + 1] <= mut);

    do
    {
        vv1->array[i] = vv1->array[i] - reb->array[i + 1];
        i++;
    }
    while (i < Nmax);
}
else //IF UP-OUT
{
    i = Nmax; //-1;
    do
    {

```



```

        vv1->array[i] = 0;
        i--;
    }
    while (y->array[i + 1] >= mut);

    do
    {
        vv1->array[i] = vv1->array[i] - reb->array[i + 1];
        i--;
    }
    while (i >= 0);
}
fft_real(vv1, 2 * kmax, -1);
vv1->array[0] = vv1->array[0] * tp1->array[0];
vv1->array[1] = vv1->array[1] * tp1->array[1];
for (i = 1; i <= kmax - 1; i++)
{
    t1 = vv1->array[2 * i];
    t2 = vv1->array[2 * i + 1];
    vv1->array[2 * i] = t1 * tp1->array[2 * i] - t2 * tp1->array[2 * i + 1];
    vv1->array[2 * i + 1] = t2 * tp1->array[2 * i] + t1 * tp1->array[2 * i + 1];
}
fft_real(vv1, 2 * kmax, 1);
for (i = 1; i < Nmax + 1; i++) // !!
{
    v1->array[i] = vv1->array[i - 1] / eom->array[i] + rebate;
    y->array[i] = y->array[i] - mut;
}

pp = log(Spot / bar);
i = 1;
while ((y->array[i] <= pp) && (i < Nx))
{
    i++;
}
i = i - 1;
//Price, quadratic interpolation
S1 = bar * exp(y->array[i - 1]);
Sm = bar * exp(y->array[i]);
Sr = bar * exp(y->array[i + 1]);
// S0 is between Sm and Sr

```

```

    pricel = v1->array[i - 1];
    pricem = v1->array[i];
    pricer = v1->array[i + 1];
    //quadratic interpolation
    A = pricel;
    B = (pricem - pricel) / (Sm - S1);
    C = (pricer - A - B * (Sr - S1)) / (Sr - S1) / (Sr - Sm);
    //Price
    *ptprice = A + B * (Spot - S1) + C * (Spot - S1) * (Spot - Sm);
    if (*ptprice < 0)
    {
        *ptprice = 0.0;
    }
    //Delta
    *ptdelta = B + C * (2 * Spot - S1 - Sm);

    //=====PREMIA_NULLTYPE=====
    /*Memory desallocation*/
    pnl_vect_free(&y);
    pnl_vect_free(&v1);
    pnl_vect_free(&vv1);
    pnl_vect_free(&tp1);
    pnl_vect_free(&alin1);
    pnl_vect_free(&tbp1);
    pnl_vect_free(&ltp1);
    pnl_vect_free(&lrm1);
    pnl_vect_free(&tbr1);
    pnl_vect_free(&tbrm1);
    pnl_vect_free(&tm1);
    pnl_vect_free(&al1);
    pnl_vect_free(&eom);
    pnl_vect_free(&reb);
    pnl_vect_free(&t);
    return OK;
}

// ////////////////////////////////// AMERICAN //////////////////////////////////
int fastwienerhopfamerican(int model, double mu, double qu, double om,
                           int ifCall, double Spot, double lm1, double lp1,
                           double num, double nup, double cnum, double cnup,
                           double r, double divid,

```

```

double T, double h, double Strike1,
double er, long int step,
double *ptprice, double *ptdelta)
{
    PnlVect *t, *y, *v1, *vv1, *tp1, *tm1,
        *tb1, *tbp1, *tbm1, *ltp1, *ltm1, *alin1, *eom, *reb, *switcharrow, *a
    long int N1 = 0, Nx, kmax, j, L;

    double pp;
    double xi, xip, xim, anp, anm, sxi, nup1 = 1., num1 = 1., abp, abm;
    double t1, t2;
    double angle;

    double a2_1 = 0.;
    double mut, emut;
    double mod;
    long int i;
    long int k;
    long int Nmax, N01;
    double dt;
    double q;
    double mu1 = 0., kx;
    double Sl, Sm, Sr;
    double pricel, pricem, pricer;
    double A, B, C;
    double sigma;

    //divid=0.0;

    if (ifCall == 0) //IF PUT
    {
        if (Spot >= 0.8 * Strike1 * exp(er * log(2.)))
        {
            *ptprice = 0.;
            *ptdelta = 0.;
            printf("Spot is out of range. Increase scale parameter \ n");
            return OK;
        }
        if (Spot <= 1.2 * Strike1 * exp(-er * log(2.)))
        {
            *ptprice = Strike1 - Spot;

```

```

        *ptdelta = -1.0;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}
else
{
    if (Spot >= 0.8 * Strike1 * exp(er * log(2.)))
    {
        *ptprice = - Strike1 + Spot;
        *ptdelta = 1.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
    if (Spot <= Strike1 * exp(-er * log(2.)) * 1.2)
    {
        *ptprice = 0.;
        *ptdelta = 0.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}

k = 64;

kx = er * log(2) / h;
while (k < kx)
{
    k = k * 2;
}
kmax = k;

N1 = step;
Nmax = 2 * kmax;
N01 = kmax;

//Memory allocation for space grid
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points
v1 = pnl_vect_create_from_zero(Nmax + 1); //prices at previous time step
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
tp1 = pnl_vect_create_from_zero(2 * kmax + 2);

```

```

alin1 = pnl_vect_create_from_zero(2 * kmax + 2);
tbp1 = pnl_vect_create_from_zero(2 * kmax + 2);
ltp1 = pnl_vect_create_from_zero(2 * kmax + 2);
ltm1 = pnl_vect_create_from_zero(2 * kmax + 2);
tb1 = pnl_vect_create_from_zero(2 * kmax + 2);
tbm1 = pnl_vect_create_from_zero(2 * kmax + 2);
tm1 = pnl_vect_create_from_zero(2 * kmax + 2);
al1 = pnl_vect_create_from_zero(2 * kmax + 2);
eom = pnl_vect_create_from_zero(Nmax + 1);
reb = pnl_vect_create_from_zero(Nmax + 1);
dividterm = pnl_vect_create_from_zero(Nmax + 1);
t = pnl_vect_create_from_zero(N1 + 2); //time points

lp1 += om;
lm1 += om;

/*Time step*/
dt = T / N1;
t->array[1] = 0;

q = qu + 1 / dt;

//===== compute coefficients
if (model == 1) /*TSL*/
{
    mu1 = mu;
    sigma = 0.;
}
if (model == 2) /*NIG*/
{
    mu1 = mu;
    sigma = 0.;
}
if (model == 3) /*VG*/
{
    mu1 = 0.0;
    sigma = 0.;
    if ((mu > 0.0) && (mu < 0.1))
    {
        mu1 = mu - 0.1;
    }
}

```

```

        if ((mu <= 0.0) && (mu > -0.1))
        {
            mu1 = mu + 0.1;
        }
        q += mu1 * om;
    }
    if (model == 4) /*KOU*/
    {
        mu1 = 0.0; //mu

        sigma = nup;
        mu += sigma * sigma * om;
        nup = num;
        cnum *= (lm1 - om) / lm1;
        cnup *= (lp1 - om) / lp1;
    }
    findcoef(model, mu - mu1, sigma, lm1, lp1, num, nup, cnum, cnup, q, r, T, h, k
//=====
    a2_1 = q * dt;

    Nx = Nmax; /*number of space points*/

    i = 0;
    do
    {
        alin1->array[i] = al1->array[i + 1];
        i++;
    }
    while (i < 2 * kmax);

    if (nup == num)
    {
        nup1 = nup / 2.0;
        num1 = num / 2.0;
    }
    if (nup > num)
    {
        nup1 = nup; // /2;
        num1 = 0.0;
    }

```

```

    }
    if (nup < num)
    {
        nup1 = 0.0; // /2;
        num1 = num;
    }
    abp = pow(lp1, nup1);
    abm = pow(-lm1, num1);

    ltp1->array[0] = 1;
    ltm1->array[0] = 1;
    xi = -M_PI / h;

    xip = pow(xi * xi + lp1 * lp1, nup1 / 2) / abp;
    xim = pow(xi * xi + lm1 * lm1, num1 / 2) / abm;
    anp = nup1 * atan(xi / lp1);
    anm = num1 * atan(xi / lm1);
    ltp1->array[1] = xip * cos(anp);
    ltm1->array[1] = xim * cos(anm);
    ltp1->array[2 * kmax] = xip * sin(anp);
    ltm1->array[2 * kmax] = xim * sin(anm);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = pow(xi * xi + lp1 * lp1, nup1 / 2) / abp;
        xim = pow(xi * xi + lm1 * lm1, num1 / 2) / abm;
        anp = nup1 * atan(xi / lp1);
        anm = num1 * atan(xi / lm1);
        ltp1->array[2 * i] = xip * cos(anp);
        ltp1->array[2 * i + 1] = xip * sin(anp);
        ltm1->array[2 * i] = xim * cos(anm);
        ltm1->array[2 * i + 1] = xim * sin(anm);
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);

    alin1->array[1] = alin1->array[1] * (ltp1->array[1] * ltm1->array[1] - ltp1->a

```

```

for (i = 1; i <= kmax - 1; i++)
{
    t1 = alin1->array[2 * i];
    t2 = alin1->array[2 * i + 1];
    alin1->array[2 * i] = t1 * ltm1->array[2 * i] - t2 * ltm1->array[2 * i + 1];
    alin1->array[2 * i + 1] = t2 * ltm1->array[2 * i] + t1 * ltm1->array[2 * i + 1];
}
for (i = 1; i <= kmax - 1; i++)
{
    t1 = alin1->array[2 * i];
    t2 = alin1->array[2 * i + 1];
    alin1->array[2 * i] = t1 * ltp1->array[2 * i] - t2 * ltp1->array[2 * i + 1];
    alin1->array[2 * i + 1] = t2 * ltp1->array[2 * i] + t1 * ltp1->array[2 * i + 1];
}

ltp1->array[0] = 1 / ltp1->array[0];
ltm1->array[0] = 1 / ltm1->array[0];
ltp1->array[1] = ltp1->array[1] / (ltp1->array[1] * ltp1->array[1] + ltp1->array[0]);
ltm1->array[1] = ltm1->array[1] / (ltm1->array[1] * ltm1->array[1] + ltm1->array[0]);

i = 1;
do
{
    mod = ltp1->array[2 * i + 1] * ltp1->array[2 * i + 1] + ltp1->array[2 * i];
    ltp1->array[2 * i + 1] = -ltp1->array[2 * i + 1] / mod;
    ltp1->array[2 * i] = ltp1->array[2 * i] / mod;

    mod = ltm1->array[2 * i + 1] * ltm1->array[2 * i + 1] + ltm1->array[2 * i];
    ltm1->array[2 * i + 1] = -ltm1->array[2 * i + 1] / mod;
    ltm1->array[2 * i] = ltm1->array[2 * i] / mod;
    i++;
}
while (i < kmax);

tb1->array[0] = log(alin1->array[0]);
tb1->array[1] = log(alin1->array[1]);

i = 1;
do
{
    mod = alin1->array[2 * i + 1] * alin1->array[2 * i + 1] + alin1->array[2 * i];

```



```

tb1->array[2 * i] = 0.5 * log(mod);
if (alin1->array[2 * i] == 0)
{
    if (alin1->array[2 * i + 1] > 0)
    {
        tb1->array[2 * i + 1] = M_PI / 2.0;
    }
    else
    {
        tb1->array[2 * i + 1] = -M_PI / 2.0;
    }
}
else
{
    angle = atan(alin1->array[2 * i + 1] / alin1->array[2 * i]);
    if (alin1->array[2 * i] > 0)
    {
        tb1->array[2 * i + 1] = angle;
    }
    if (alin1->array[2 * i] < 0)
    {
        if (alin1->array[2 * i + 1] < 0)
        {
            tb1->array[2 * i + 1] = angle - M_PI;
        }
        else
        {
            tb1->array[2 * i + 1] = angle + M_PI;
        }
    }
}
i++;
}
while (i < kmax);

i = 0;
do
{
    alin1->array[i] = al1->array[i + 1];
    i++;
}

```

```

while (i < 2 * kmax);

fft_real(tb1, 2 * kmax, 1);

i = 1;
tbp1->array[0] = 0;
tbm1->array[0] = 0;
do
{
    tbp1->array[0] = tbp1->array[0] - tb1->array[i];
    tbp1->array[i] = tb1->array[i];
    tbm1->array[i] = 0;
    i++;
}
while (i < kmax);
do
{
    tbm1->array[i] = tb1->array[i];
    tbp1->array[i] = 0;
    tbm1->array[0] = tbm1->array[0] - tb1->array[i];
    i++;
}
while (i < 2 * kmax);

fft_real(tbp1, 2 * kmax, -1);
fft_real(tbm1, 2 * kmax, -1);

tp1->array[0] = exp(tbp1->array[0]);
tp1->array[1] = exp(tbp1->array[1]);
tm1->array[0] = exp(tbm1->array[0]);
tm1->array[1] = exp(tbm1->array[1]);

i = 1;
do
{
    mod = exp(tbp1->array[2 * i]);
    tp1->array[2 * i] = mod * cos(tbp1->array[2 * i + 1]);
    tp1->array[2 * i + 1] = mod * sin(tbp1->array[2 * i + 1]);
    mod = exp(tbm1->array[2 * i]);
    tm1->array[2 * i] = mod * cos(tbm1->array[2 * i + 1]);

```

```

        tm1->array[2 * i + 1] = mod * sin(tbm1->array[2 * i + 1]);
        i++;
    }
    while (i < kmax);

    tp1->array[0] = tp1->array[0] * ltp1->array[0];
    tp1->array[1] = tp1->array[1] * ltp1->array[1];

    tm1->array[0] = tm1->array[0] * ltm1->array[0];
    tm1->array[1] = tm1->array[1] * ltm1->array[1];

    for (i = 1; i <= kmax - 1; i++)
    {
        t1 = tm1->array[2 * i];
        t2 = tm1->array[2 * i + 1];
        tm1->array[2 * i] = t1 * ltm1->array[2 * i] - t2 * ltm1->array[2 * i + 1];
        tm1->array[2 * i + 1] = t2 * ltm1->array[2 * i] + t1 * ltm1->array[2 * i + 1];
    }
    for (i = 1; i <= kmax - 1; i++)
    {
        t1 = tp1->array[2 * i];
        t2 = tp1->array[2 * i + 1];
        tp1->array[2 * i] = t1 * ltp1->array[2 * i] - t2 * ltp1->array[2 * i + 1];
        tp1->array[2 * i + 1] = t2 * ltp1->array[2 * i] + t1 * ltp1->array[2 * i + 1];
    }

    if (ifCall == 0)
    {
        for (j = 1; j <= Nmax; j++)
        {
            y->array[j] = (j - N01 - 0.5) * h;
            vv1->array[j - 1] = 0;
            eom->array[j] = exp(-om * y->array[j]);
            reb->array[j] = Strike1 * dt * r * eom->array[j];
            dividterm->array[j] = -Strike1 * divid * dt * eom->array[j] * exp(y->a
        }
    }
    else
    {
        for (j = 1; j <= Nmax; j++)

```

```

        {
            y->array[j] = (j - N01 + 0.5) * h;
            vv1->array[j - 1] = 0;
            eom->array[j] = exp(-om * y->array[j]);
            reb->array[j] = -Strike1 * dt * r * eom->array[j];
            dividterm->array[j] = Strike1 * divid * dt * eom->array[j] * exp(y->ar
        }
    }

if (ifCall == 0)
{
    j = kmax + 1;
    do
    {
        vv1->array[j - 1] = (-Strike1 + Strike1 * exp(y->array[j])) * eom->arra
        j++;
    }
    while (j <= Nmax);
}
else
{
    j = kmax - 1;
    do
    {
        vv1->array[j - 1] = (Strike1 - Strike1 * exp(y->array[j])) * eom->arra
        j--;
    }
    while (j > 0);
}

//===== EXCHANGE tp AND tm ARRAYS FOR UP-OUT
if (ifCall == 1)
{
    switcharrow = tp1;
    tp1 = tm1;
    tm1 = switcharrow;
}
//=====

for (i = 0; i < Nmax; i++)

```

```

    {
        tp1->array[i] = tp1->array[i] / a2_1;
        alin1->array[i] = alin1->array[i] / a2_1;
    }

fft_real(vv1, 2 * kmax, -1);

vv1->array[0] = vv1->array[0] * tm1->array[0];
vv1->array[1] = vv1->array[1] * tm1->array[1];

for (i = 1; i <= kmax - 1; i++)
{
    t1 = vv1->array[2 * i];
    t2 = vv1->array[2 * i + 1];
    vv1->array[2 * i] = t1 * tm1->array[2 * i] - t2 * tm1->array[2 * i + 1];
    vv1->array[2 * i + 1] = t2 * tm1->array[2 * i] + t1 * tm1->array[2 * i + 1];
}
fft_real(vv1, 2 * kmax, 1);

//=====Main Loop on time grid=====/

for (L = 2; L <= N1; L++)
{
    t->array[L] = t->array[L - 1] + dt;

    mut = t->array[L] * mu1;
    emut = exp(-mut);

    i = Nmax - 1;
    do
    {
        vv1->array[i] = vv1->array[i] - reb->array[i + 1] - dividterm->array[i];
        if (vv1->array[i] < 0)
        {
            vv1->array[i] = 0;
        }
        i--;
    }
    while (i >= 0);
}

```

```

fft_real(vv1, 2 * kmax, -1);

vv1->array[0] = vv1->array[0] * alin1->array[0];
vv1->array[1] = vv1->array[1] * alin1->array[1];

for (i = 1; i <= kmax - 1; i++)
{
    t1 = vv1->array[2 * i];
    t2 = vv1->array[2 * i + 1];
    vv1->array[2 * i] = t1 * alin1->array[2 * i] - t2 * alin1->array[2 * i + 1];
    vv1->array[2 * i + 1] = t2 * alin1->array[2 * i] + t1 * alin1->array[2 * i + 1];
}

fft_real(vv1, 2 * kmax, 1);
} // ===== PREMIA_NULLTYPE MAIN LOOP =====

t->array[N1 + 1] = t->array[N1] + dt;
mut = mu1 * t->array[N1 + 1];
emut = exp(-mut);

i = Nmax - 1;
do
{
    vv1->array[i] = (vv1->array[i] - reb->array[i + 1]) - dividterm->array[i + 1];
    if (vv1->array[i] < 0)
    {
        vv1->array[i] = 0;
    }
    i--;
}
while (i >= 0);

fft_real(vv1, 2 * kmax, -1);
vv1->array[0] = vv1->array[0] * tp1->array[0];
vv1->array[1] = vv1->array[1] * tp1->array[1];

for (i = 1; i <= kmax - 1; i++)
{
    t1 = vv1->array[2 * i];
    t2 = vv1->array[2 * i + 1];
    vv1->array[2 * i] = t1 * tp1->array[2 * i] - t2 * tp1->array[2 * i + 1];

```

```

        vv1->array[2 * i + 1] = t2 * tp1->array[2 * i] + t1 * tp1->array[2 * i + 1]
    }
    fft_real(vv1, 2 * kmax, 1);

    if (ifCall == 0)
    {
        for (i = 1; i < Nmax + 1; i++)
        {
            y->array[i] = y->array[i] - mut;
            v1->array[i] = vv1->array[i - 1] / eom->array[i] + Strike1 - Strike1 *
        }
    }
    else
    {
        for (i = 1; i < Nmax + 1; i++)
        {
            y->array[i] = y->array[i] - mut;
            v1->array[i] = vv1->array[i - 1] / eom->array[i] - Strike1 + Strike1 *
        }
    }

    pp = log(Spot / Strike1);

    i = 1;

    while ((y->array[i] <= pp) && (i < Nx))
    {
        i++;
    }
    i = i - 1;
    //Price, quadratic interpolation
    Sl = Strike1 * exp(y->array[i - 1]);
    Sm = Strike1 * exp(y->array[i]);
    Sr = Strike1 * exp(y->array[i + 1]);

    // S0 is between Sm and Sr
    pricel = v1->array[i - 1];
    pricem = v1->array[i];
    pricer = v1->array[i + 1];

    //quadratic interpolation

```

```

A = pricel;
B = (pricem - pricel) / (Sm - Sl);
C = (pricer - A - B * (Sr - Sl)) / (Sr - Sl) / (Sr - Sm);

//Price
*ptprice = A + B * (Spot - Sl) + C * (Spot - Sl) * (Spot - Sm);
if (*ptprice < 0)
{
    *ptprice = 0.0;
}
//Delta
*ptdelta = B + C * (2 * Spot - Sl - Sm);

//=====PREMIA_NULLTYPE=====
/*Memory deallocation*/
pnl_vect_free(&y);
pnl_vect_free(&v1);
pnl_vect_free(&vv1);
pnl_vect_free(&tp1);
pnl_vect_free(&alin1);
pnl_vect_free(&tbp1);
pnl_vect_free(&ltp1);
pnl_vect_free(&ltm1);
pnl_vect_free(&tb1);
pnl_vect_free(&tbm1);
pnl_vect_free(&tm1);
pnl_vect_free(&al1);
pnl_vect_free(&eom);
pnl_vect_free(&reb);
pnl_vect_free(&t);
pnl_vect_free(&dividterm);

return OK;
}

```

```

//Code for Backward Fourier

```

```

//=====

```

```

static int findcoef_bi(int model, double mu, double sigma, double lm1, double lp
                        double num, double nup,
                        double cnum, double cnup, double q, double r1,

```



```

double T, double h, long int kmax,
long int Nt,
PnlVect *bl1)

{
    //PnlVect *bl1;
    long int i;
    double mod;
    //PnlVect *alin1;
    double xi, xip, xim, anp, anm, sxi, nup1, num1;
    double lpm1;

    double del1;
    double sg2;
    double cpl;    // !!!!!
    double cml;

    /*Memory allocation for space grid*/

    // bl1=pnl_vect_create(2*kmax+1);

    del1 = -T / Nt;
    /////////////////////////////////// this part depends on model
    if (model == 1/*TSL*/)
    {
        lpm1 = q + pow(lp1, nup) * cnup + pow(-lm1, num) * cnum;

        nup1 = nup / 2;
        num1 = num / 2;
        bl1->array[0] = q;
        xi = -M_PI / h;
        xip = pow(xi * xi + lp1 * lp1, nup1);
        xim = pow(xi * xi + lm1 * lm1, num1);
        anp = nup * atan(xi / lp1);
        anm = num * atan(xi / lm1);
        bl1->array[1] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm);
        bl1->array[2 * kmax] = -cnup * xip * sin(anp) - cnum * xim * sin(anm) - mu
        sxi = xi / kmax;
        xi = sxi;
    }
}

```

```

i = 1;
do
{
    xip = pow(xi * xi + lp1 * lp1, nup1);
    xim = pow(xi * xi + lm1 * lm1, num1);
    anp = nup * atan(xi / lp1);
    anm = num * atan(xi / lm1);
    bl1->array[2 * i] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm);
    bl1->array[2 * i + 1] = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
    i++;
    xi = xi + sxi;
}
while (i < kmax);
} // END TSL
if (model == 2/*NIG*/)
{
    lpm1 = q - sqrt(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = 0.5 * atan(xim / xip);
    bl1->array[1] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
    bl1->array[2 * kmax] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;
        xim = -(lp1 + lm1) * xi;
        anp = 0.5 * atan(xim / xip);
        bl1->array[2 * i] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
        bl1->array[2 * i + 1] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END NIG

```

```

if (model == 3/*VGP*/)
{
    lpm1 = q - log(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = atan(xim / xip);
    bl1->array[1] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
    bl1->array[2 * kmax] = cnup * anp - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;
        xim = -(lp1 + lm1) * xi;
        anp = atan(xim / xip);
        bl1->array[2 * i] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
        bl1->array[2 * i + 1] = cnup * anp - mu * xi;
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END VGP
if (model == 4/*KOU*/)
{
    // nup==sigma
    sg2 = sigma * sigma / 2;
    cpl = cnup * lp1; // !!!!!
    cml = cnum * lm1;

    //lpm1=q+pow(lp1,nup)*cnup+pow(-lm1,num)*cnum;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi + lp1 * lp1;
    xim = xi * xi + lm1 * lm1;
    bl1->array[1] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;

```

```

    bl1->array[2 * kmax] = xi * (cpl / xip + cml / xim) - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi + lp1 * lp1;
        xim = xi * xi + lm1 * lm1;
        bl1->array[2 * i] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
        bl1->array[2 * i + 1] = xi * (cpl / xip + cml / xim) - mu * xi;
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);

} // END KOU
////////////////////////////////////
bl1->array[0] = exp(del1 * bl1->array[0]);
bl1->array[1] = exp(del1 * bl1->array[1]);
i = 1;
do
{
    bl1->array[2 * i] = exp(del1 * bl1->array[2 * i]);
    mod = del1 * bl1->array[2 * i + 1];
    bl1->array[2 * i + 1] = bl1->array[2 * i] * sin(mod);
    bl1->array[2 * i] = bl1->array[2 * i] * cos(mod);
    i++;
}
while (i < kmax);

return 1;
}

//////////////////////////////// Code for VAR coef //////////////////////////////////
//=====
static int findcoef_var(int model, double mu, double sigma, double lm1, double l
    double num, double nup,
    double cnum, double cnup, double q,
    double T, double h, long int kmax,
    long int Nt,

```

```

                                PnlVect *bl1)

{
    long int i;
    double mod;
    double xi, xip, xim, anp, anm, sxi, nup1, num1;
    double lpm1;

    double del1;
    double sg2;
    double cpl;
    double cml;

    del1 = -T / Nt;
    /////////////////////////////////// this part depends on model
    if (model == 1/*TSL*/)
    {

        lpm1 = q + pow(lp1, nup) * cnup + pow(-lm1, num) * cnum;

        nup1 = nup / 2;
        num1 = num / 2;
        bl1->array[0] = q;
        xi = M_PI / h;
        xip = pow(xi * xi + lp1 * lp1, nup1);
        xim = pow(xi * xi + lm1 * lm1, num1);
        anp = nup * atan(xi / lp1);
        anm = num * atan(xi / lm1);
        bl1->array[1] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(anm);
        bl1->array[2 * kmax] = -cnup * xip * sin(anp) - cnum * xim * sin(anm) - mu;
        sxi = xi / kmax;
        xi = sxi;

        i = 1;
        do
        {
            xip = pow(xi * xi + lp1 * lp1, nup1);
            xim = pow(xi * xi + lm1 * lm1, num1);
            anp = nup * atan(xi / lp1);
            anm = num * atan(xi / lm1);
            bl1->array[2 * i] = lpm1 - cnup * xip * cos(anp) - cnum * xim * cos(an

```

```

        bl1->array[2 * i + 1] = -cnup * xip * sin(anp) - cnum * xim * sin(anm);
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END TSL
if (model == 2/*NIG*/)
{
    lpm1 = q - sqrt(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = 0.5 * atan(xim / xip);
    bl1->array[1] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
    bl1->array[2 * kmax] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi - lp1 * lm1;
        xim = -(lp1 + lm1) * xi;
        anp = 0.5 * atan(xim / xip);
        bl1->array[2 * i] = lpm1 + cnum * pow(xip * xip + xim * xim, 0.25) * cos(anp);
        bl1->array[2 * i + 1] = cnup * pow(xip * xip + xim * xim, 0.25) * sin(anp);
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);
} // END NIG
if (model == 3/*VGP*/)
{
    lpm1 = q - log(-lp1 * lm1) * cnup;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;

```

```

anp = atan(xim / xip);
bl1->array[1] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
bl1->array[2 * kmax] = cnup * anp - mu * xi;
sxi = xi / kmax;
xi = sxi;

i = 1;
do
{
    xip = xi * xi - lp1 * lm1;
    xim = -(lp1 + lm1) * xi;
    anp = atan(xim / xip);
    bl1->array[2 * i] = lpm1 + cnup * log(xip * xip + xim * xim) / 2;
    bl1->array[2 * i + 1] = cnup * anp - mu * xi;
    i++;
    xi = xi + sxi;
}
while (i < kmax);
} // END VGP
if (model == 4/*KOU*/)
{

    sg2 = sigma * sigma / 2;
    cpl = cnup * lp1;
    cml = cnum * lm1;

    bl1->array[0] = q;
    xi = -M_PI / h;
    xip = xi * xi + lp1 * lp1;
    xim = xi * xi + lm1 * lm1;
    bl1->array[1] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;
    bl1->array[2 * kmax] = xi * (cpl / xip + cml / xim) - mu * xi;
    sxi = xi / kmax;
    xi = sxi;

    i = 1;
    do
    {
        xip = xi * xi + lp1 * lp1;
        xim = xi * xi + lm1 * lm1;
        bl1->array[2 * i] = q + (sg2 + cnup / xip + cnum / xim) * xi * xi;

```

```

        bl1->array[2 * i + 1] = xi * (cpl / xip + cml / xim) - mu * xi;
        i++;
        xi = xi + sxi;
    }
    while (i < kmax);

} // END KOU
////////////////////////////////////
bl1->array[0] = exp(del1 * bl1->array[0]);
bl1->array[1] = exp(del1 * bl1->array[1]);
i = 1;
do
{
    bl1->array[2 * i] = exp(del1 * bl1->array[2 * i]);
    mod = del1 * bl1->array[2 * i + 1];
    bl1->array[2 * i + 1] = bl1->array[2 * i] * sin(mod);
    bl1->array[2 * i] = bl1->array[2 * i] * cos(mod);
    i++;
}
while (i < kmax);

return 1;
}
int expectation(long int kmax, PnlVect *vv1, PnlVect *bl1)
{
    long int i;
    double t1, t2;

    vv1->array[0] = vv1->array[0] * bl1->array[0];
    vv1->array[1] = vv1->array[1] * bl1->array[1];

    for (i = 1; i <= kmax - 1; i++)
    {
        t1 = vv1->array[2 * i];
        t2 = vv1->array[2 * i + 1];
        vv1->array[2 * i] = t1 * bl1->array[2 * i] - t2 * bl1->array[2 * i + 1];
        vv1->array[2 * i + 1] = t2 * bl1->array[2 * i] + t1 * bl1->array[2 * i + 1];
    }
    fft_real(vv1, 2 * kmax, 1);

```



```

    return 1;
}

```

```

/*//////////////////////// BARRIER AND DIGITAL Backward induction////////////////////////////////////

```

```

int bi_barr(double mu, double qu, double om, int upordown, int ifCall, double Sp,
            double num, double nup, double cnum, double cnup,
            double r, double divid,
            double T, double h, double Strike1,
            double bar, double rebate,
            double er, long int step,
            double *ptprice, double *ptdelta)
{
    PnlVect *y, * v1, *vv1, *eom, *reb, *al1;
    long int N1 = 0, Nx, kmax, j, L;

    double pp;
    long int i;
    long int k;
    long int Nmax, N01;
    double dt;

    double q;
    double str, kx;
    double Sl, Sm, Sr;
    double pricel, pricem, pricer;
    double A, B, C;

    if (upordown == 0)
    {
        if (Spot <= bar)
        {
            *ptprice = rebate;
            *ptdelta = 0.;
            return OK;
        }
        if (Spot >= 0.8 * bar * exp(er * log(2.)))

```

```

        {
            *ptprice = 0.;
            *ptdelta = 0.;
            printf("Spot is out of range. Increase scale parameter \ n");
            return OK;
        }
    }
else
{
    if (Spot >= bar)
    {
        *ptprice = rebate;
        *ptdelta = 0.;
        return OK;
    }
    if (Spot <= bar * exp(-er * log(2.)) * 1.2)
    {
        *ptprice = 0.;
        *ptdelta = 0.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}

str = log(Strike1 / bar);

k = 64;

kx = er * log(2) / h;
while (k < kx)
{
    k = k * 2;
}
kmax = k;

N1 = step;
Nmax = 2 * kmax;
N01 = kmax;      //   !!!kmax

//Memory allocation for space grid
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points

```

```

v1 = pnl_vect_create_from_zero(Nmax + 1); //prices at previous time step
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
all = pnl_vect_create_from_zero(2 * kmax + 2);
eom = pnl_vect_create_from_zero(Nmax + 1);
reb = pnl_vect_create_from_zero(Nmax + 1);
//t=pnl_vect_create_from_zero(N1+2); //time points

lp1 += om;
lm1 += om;

/*Time step*/
dt = T / N1;
// t->array[1]=0;

q = qu;

//===== compute coefficients
findcoef_bi(3, mu, 0., lm1, lp1, num, nup, cnum, cnup, q, r, T, h, kmax, N1, a
//=====

Nx = Nmax; /*number of space points*/

/*Put Pay-off functions*/
if (upordown == 0)
    for (j = 1; j <= kmax; j++)
    {
        y->array[j] = (j - N01 - 0.5) * h;
        vv1->array[j - 1] = 0;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
    }
else
    for (j = kmax; j <= Nmax; j++)
    {
        y->array[j] = (j - N01 + 0.5) * h;
        vv1->array[j - 1] = 0;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
    }

```

```

if (upordown == 0) // IF DOWN-OUT
{
    j = kmax + 1;

    if (ifCall == 2) /* DIGITAL */
    {
        do
        {
            y->array[j] = (j - N01 - 0.5) * h;
            eom->array[j] = exp(-om * y->array[j]);
            reb->array[j] = rebate * dt * r * eom->array[j];

            vv1->array[j - 1] = -rebate * eom->array[j];
            j++;
        }
        while (j <= Nmax);
    }
    else if (ifCall == 1) /* CALL */
    {
        do
        {
            y->array[j] = (j - N01 - 0.5) * h;
            eom->array[j] = exp(-om * y->array[j]);
            reb->array[j] = rebate * dt * r * eom->array[j];
            if (y->array[j] >= str)
            {
                vv1->array[j - 1] = (-Strike1 + bar * exp(y->array[j]) - rebat
            }
            else
            {
                vv1->array[j - 1] = -rebate * eom->array[j];
            }
            j++;
        }
        while (j <= Nmax);
    }
    else /* PUT */
    {
        do
        {

```

```

        y->array[j] = (j - N01 - 0.5) * h;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
        if (y->array[j] <= str)
        {
            vv1->array[j - 1] = (Strike1 - bar * exp(y->array[j]) - rebate
        }
        else
        {
            vv1->array[j - 1] = -rebate * eom->array[j];
        }
        j++;
    }
    while (j <= Nmax);
}
} // END IF DOWN-OUT
else // IF UP-OUT
{
    j = kmax - 1;

    if (ifCall == 2) /* DIGITAL */
    {
        do
        {
            y->array[j] = (j - N01 + 0.5) * h;
            eom->array[j] = exp(-om * y->array[j]);
            reb->array[j] = rebate * dt * r * eom->array[j];

            {
                vv1->array[j - 1] = -rebate * eom->array[j];
            }
            j--;
        }
        while (j > 0);
    }
    else if (ifCall == 1) /* CALL */
    {
        do
        {
            y->array[j] = (j - N01 + 0.5) * h;
            eom->array[j] = exp(-om * y->array[j]);

```

```

        reb->array[j] = rebate * dt * r * eom->array[j];
        if (y->array[j] >= str)
        {
            vv1->array[j - 1] = (-Strike1 + bar * exp(y->array[j])) - rebate;
        }
        else
        {
            vv1->array[j - 1] = -rebate * eom->array[j];
        }
        j--;
    }
    while (j > 0);
}
else /* PUT */
{
    do
    {
        y->array[j] = (j - N01 + 0.5) * h;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = rebate * dt * r * eom->array[j];
        if (y->array[j] <= str)
        {
            vv1->array[j - 1] = (Strike1 - bar * exp(y->array[j])) - rebate;
        }
        else
        {
            vv1->array[j - 1] = -rebate * eom->array[j];
        }
        j--;
    }
    while (j > 0);
}

} // END IF UP

/*Main Loop on time grid*/

for (L = 1; L <= N1; L++)
{
    fft_real(vv1, 2 * kmax, -1);

```

```

expectation(kmax, vv1, al1);
if (upordown == 0) // IF DOWN-OUT                                !!
{
    i = 0;
    do
    {
        vv1->array[i] = 0;
        i++;
    }
    while (y->array[i + 1] <= 0);

    do
    {
        vv1->array[i] = vv1->array[i] - reb->array[i + 1];
        i++;
    }
    while (i < Nmax);
}
else //IF UP-OUT
{
    i = Nmax; //-1;
    do
    {
        vv1->array[i] = 0;
        i--;
    }
    while (y->array[i + 1] >= 0);

    do
    {
        vv1->array[i] = vv1->array[i] - reb->array[i + 1];
        i--;
    }
    while (i >= 0);
}

} // END MAIN LOOP

for (i = 1; i < Nmax + 1; i++)                                // !!
{

```

```

    v1->array[i] = vv1->array[i - 1] / eom->array[i] + rebate;
}

pp = log(Spot / bar);
i = 1;
while ((y->array[i] <= pp) && (i < Nx))
{
    i++;
}
//Price, quadratic interpolation
S1 = bar * exp(y->array[i - 1]);
Sm = bar * exp(y->array[i]);
Sr = bar * exp(y->array[i + 1]);
// S0 is between Sm and Sr
pricel = v1->array[i - 1];
pricem = v1->array[i];
pricer = v1->array[i + 1];
//quadratic interpolation
A = pricel;
B = (pricem - pricel) / (Sm - S1);
C = (pricer - A - B * (Sr - S1)) / (Sr - S1) / (Sr - Sm);
//Price
*ptprice = A + B * (Spot - S1) + C * (Spot - S1) * (Spot - Sm);
if (*ptprice < 0)
{
    *ptprice = 0.0;
}
//Delta
*ptdelta = B + C * (2 * Spot - S1 - Sm);

//=====END=====
/*Memory deallocation*/
pnl_vect_free(&y);
pnl_vect_free(&v1);
pnl_vect_free(&vv1);
pnl_vect_free(&a11);
pnl_vect_free(&eom);
pnl_vect_free(&reb);
return OK;
}

```



```

// ////////////////////////////////// AMERICAN Backward induction////////////////////////////////////

int bi_american(double mu, double qu, double om,
                int ifCall, double Spot, double lm1, double lp1,
                double num, double nup, double cnum, double cnp,
                double r, double divid,
                double T, double h, double Strike1,
                double er, long int step,
                double *ptprice, double *ptdelta)
{
    PnlVect *y, *v1, *vv1, *eom, *reb, *a11, *dividterm;
    long int N1 = 0, Nx, kmax, j, L;

    double pp;

    //double mut, emut;
    long int i;
    long int k;
    long int Nmax, N01;
    double dt;
    double q;
    double kx;
    double Sl, Sm, Sr;
    double pricel, pricem, pricer;
    double A, B, C;

    //divid=0.0;

    if (ifCall == 0) //IF PUT
    {
        if (Spot >= 0.8 * Strike1 * exp(er * log(2.)))
        {
            *ptprice = 0.;
            *ptdelta = 0.;
            printf("Spot is out of range. Increase scale parameter \ n");
            return OK;
        }
        if (Spot <= 1.2 * Strike1 * exp(-er * log(2.)))
        {
            *ptprice = Strike1 - Spot;

```

```

        *ptdelta = -1.0;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}
else
{
    if (Spot >= 0.8 * Strike1 * exp(er * log(2.)))
    {
        *ptprice = - Strike1 + Spot;
        *ptdelta = 1.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
    if (Spot <= Strike1 * exp(-er * log(2.)) * 1.2)
    {
        *ptprice = 0.;
        *ptdelta = 0.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}

k = 64;

kx = er * log(2) / h;
while (k < kx)
{
    k = k * 2;
}
kmax = k;

N1 = step;
Nmax = 2 * kmax;
N01 = kmax;

//Memory allocation for space grid
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points
v1 = pnl_vect_create_from_zero(Nmax + 1); //prices at previous time step
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
a11 = pnl_vect_create_from_zero(2 * kmax + 2);

```

```

eom = pnl_vect_create_from_zero(Nmax + 1);
reb = pnl_vect_create_from_zero(Nmax + 1);
dividterm = pnl_vect_create_from_zero(Nmax + 1);
//t=pnl_vect_create_from_zero(N1+2); //time points

lp1 += om;
lm1 += om;

/*Time step*/
dt = T / N1;
//t->array[1]=0;

q = qu;

//===== compute coefficients
findcoef_bi(3, mu, 0., lm1, lp1, num, nup, cnum, cnup, q, r, T, h, kmax, N1, a
//=====

Nx = Nmax; /*number of space points*/

/*Pay-off functions*/

if (ifCall == 0)
{
    for (j = 1; j <= Nmax; j++)
    {
        y->array[j] = (j - N01 - 0.5) * h;
        vv1->array[j - 1] = 0;
        eom->array[j] = exp(-om * y->array[j]);
        reb->array[j] = Strike1 * dt * r * eom->array[j];
        dividterm->array[j] = -Strike1 * divid * dt * eom->array[j] * exp(y->a
    }
}
else
{
    for (j = 1; j <= Nmax; j++)
    {
        y->array[j] = (j - N01 + 0.5) * h;
        vv1->array[j - 1] = 0;
        eom->array[j] = exp(-om * y->array[j]);

```

```

        reb->array[j] = -Strike1 * dt * r * eom->array[j];
        dividterm->array[j] = Strike1 * divid * dt * eom->array[j] * exp(y->ar
    }
}

if (ifCall == 0)
{
    j = kmax + 1;
    do
    {
        vv1->array[j - 1] = (-Strike1 + Strike1 * exp(y->array[j])) * eom->arr
        j++;
    }
    while (j <= Nmax);
}
else
{
    j = kmax - 1;
    do
    {
        vv1->array[j - 1] = (Strike1 - Strike1 * exp(y->array[j])) * eom->arra
        j--;
    }
    while (j > 0);
}

//=====Main Loop on time grid=====

for (L = 1; L <= N1; L++)
{
    fft_real(vv1, 2 * kmax, -1);
    expectation(kmax, vv1, al1);

    i = Nmax - 1;
    do
    {
        vv1->array[i] = vv1->array[i] - reb->array[i + 1] - dividterm->array[i]
        if (vv1->array[i] < 0)
        {
            vv1->array[i] = 0;
        }
    }
}

```

```

        i--;
    }
    while (i >= 0);
} // ===== END MAIN LOOP =====

if (ifCall == 0)
{
    for (i = 1; i < Nmax + 1; i++)
    {
        v1->array[i] = vv1->array[i - 1] / eom->array[i] + Strike1 - Strike1 *
    }
}
else
{
    for (i = 1; i < Nmax + 1; i++)
    {
        v1->array[i] = vv1->array[i - 1] / eom->array[i] - Strike1 + Strike1 *
    }
}

pp = log(Spot / Strike1);

i = 1;

while ((y->array[i] <= pp) && (i < Nx))
{
    i++;
}

//Price, quadratic interpolation
S1 = Strike1 * exp(y->array[i - 1]);
Sm = Strike1 * exp(y->array[i]);
Sr = Strike1 * exp(y->array[i + 1]);

// S0 is between Sm and Sr
pricel = v1->array[i - 1];
pricem = v1->array[i];
pricer = v1->array[i + 1];

//quadratic interpolation
A = pricel;

```

```

B = (pricem - pricel) / (Sm - Sl);
C = (pricer - A - B * (Sr - Sl)) / (Sr - Sl) / (Sr - Sm);

//Price
*ptprice = A + B * (Spot - Sl) + C * (Spot - Sl) * (Spot - Sm);
if (*ptprice < 0)
{
    *ptprice = 0.0;
}
//Delta
*ptdelta = B + C * (2 * Spot - Sl - Sm);

//=====END=====
/*Memory deallocation*/
pnl_vect_free(&y);
pnl_vect_free(&v1);
pnl_vect_free(&vv1);
pnl_vect_free(&a11);
pnl_vect_free(&eom);
pnl_vect_free(&reb);
pnl_vect_free(&dividterm);

return OK;
}

int lookback_fls(int model, double mu, double qu, double om, int ifCall, double
                double num, double nup, double cnum, double cnup,
                double r, double divid,
                double T, double h,
                double er, double *ptprice, double *ptdelta)
{
    PnlVect *y, *vv0, *vv1, *tp1, *tm1, *coef,
            *alin1, *al1;
    long int N1 = 0, Nx, kmax, j;

    double pp;
    double a2_1 = 0.;
    int nn, n; //Laplace gs
    long int i;
    long int k;

```

```

long int Nmax;
double dt;

double q;
double mu1, kx;
double Sl, Sm, Sr;
double pricel, pricem, pricer;
double price, delta;
double A, B, C;
double sigma;

k = 64;

kx = er * log(2.0) / h;
while (k < kx)
{
    k = k * 2;
}
kmax = k;

nn = 14;    //gs
// N1=step;
Nmax = 2 * kmax;

//Memory allocation for space grid
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points
vv0 = pnl_vect_create_from_zero(Nmax + 1);
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
al1 = pnl_vect_create_from_zero(2 * kmax + 2);
alin1 = pnl_vect_create_from_zero(2 * kmax + 2);
tp1 = pnl_vect_create_from_zero(2 * kmax + 2);
tm1 = pnl_vect_create_from_zero(2 * kmax + 2);
coef = pnl_vect_create_from_zero(nn + 1); // gs
//eom=pnl_vect_create_from_zero(Nmax+1);

```

```

lp1 += om;
lm1 += om;
q = qu;

//===== compute coefficients
if (model == 1)
{
    mu1 = 0;
    sigma = 0.;
}
/*if(model == 2){
    mu1=mu;
    sigma=0.;
}
if(model == 3){
    mu1=0.0;
    sigma=0.;
    if((mu>0.0)&&(mu<0.1)) {mu1=mu-0.1;}
    if((mu<=0.0)&&(mu>-0.1)) {mu1=mu+0.1;}
    q+= mu1*om;
}*/
if (model == 4) /*KOU*/
{
    mu1 = 0.0; //mu

    sigma = nup;
    mu += sigma * sigma * om;
    nup = num;
    cnum *= (lm1 - om) / lm1;
    cnup *= (lp1 - om) / lp1;
}
if (ifCall == 1)
{
    for (j = 0; j < Nmax; j++)
    {
        y->array[j] = (j - kmax) * h;
        if (y->array[j] > 0)
        {
            vv0->array[j] = 0;
        }
        else

```



```

        {
            vv0->array[j] = 1.0 - exp(y->array[j]);
        }
    }
}
if (ifCall == 0)
{
    for (j = 0; j < Nmax; j++)
    {
        y->array[j] = (j - kmax) * h;
        if (y->array[j] < 0)
        {
            vv0->array[j] = 0;
        }
        else
        {
            vv0->array[j] = exp(y->array[j]) - 1.0;
        }
    }
}

```

```
fft_real(vv0, 2 * kmax, -1);
```

```

//-----weights-----
coef->array[1] = 0.00277778;
coef->array[2] = -6.40277778;
coef->array[3] = 924.05000000;
coef->array[4] = -34597.92777778;
coef->array[5] = 540321.11111111;
coef->array[6] = -4398346.36666666;
coef->array[7] = 21087591.77777770;
coef->array[8] = -63944913.04444440;
coef->array[9] = 127597579.55000000;
coef->array[10] = -170137188.08333300;
coef->array[11] = 150327467.03333300;
coef->array[12] = -84592161.50000000;
coef->array[13] = 27478884.76666660;
coef->array[14] = -3925554.96666666;
//-----

```

```

*ptprice = 0;
*ptdelta = 0;

//-----loop in weighted
for (n = 1; n <= nn;) // for(n=1; n<=nn;)
{
    /*Time step*/
    dt = T / (log(2.0) * n); //gs
// cout<<dt<<endl;
    q = qu + 1 / dt;

    findcoefnew(model, mu - mu1, sigma, lm1, lp1, num, nup, cnum, cnup, q, r,
//=====
// a2_1=q*dt;
    a2_1 = q;

    Nx = Nmax; /*number of space points*/

    for (i = 0; i < 2 * kmax; i++) alin1->array[i] = al1->array[i + 1];

    if (model == 1)
    {
        /*TSL*/ findfactor(0.0, 0.0, h, kmax, lp1, lm1, alin1, tp1, tm1);
    }
    if (model == 4)
    {
        /*KOU*/ findfactor(2.0, 2.0, h, kmax, lp1, lm1, alin1, tp1, tm1);
    }

//if(model == 1){/*TSL*/ factorslb(lm1, lp1, h, 0.0, 0.0, kmax, alin1, tp1);}
//if(model == 4){/*KOU*/ factorslb(lm1, lp1, h, 2.0, 2.0, kmax, alin1, tp1);}
//=====
    if (ifCall == 1)
    {
        for (i = 0; i < Nmax; i++)
        {
            tp1->array[i] = tp1->array[i] / a2_1;
            vv1->array[i] = vv0->array[i];
        }
        expectation(kmax, vv1, tp1);
        /* vv1->array[0]= vv1->array[0]*tp1->array[0];

```

```

vv1->array[1]= vv1->array[1]*tp1->array[1];

for(i = 1; i <= kmax-1; i++)
{
    t1 = vv1->array[2*i];
    t2 = vv1->array[2*i+1];
    vv1->array[2*i]= t1*tp1->array[2*i]-t2*tp1->array[2*i+1];
    vv1->array[2*i+1]= t2*tp1->array[2*i]+t1*tp1->array[2*i+1];
}*/
}
if (ifCall == 0)
{
    for (i = 0; i < Nmax; i++)
    {
        tm1->array[i] = tm1->array[i] / a2_1;
        vv1->array[i] = vv0->array[i];
    }
    expectation(kmax, vv1, tm1);
    /* vv1->array[0]= vv1->array[0]*tm1->array[0];
    vv1->array[1]= vv1->array[1]*tm1->array[1];

    for(i = 1; i <= kmax-1; i++)
    {
        t1 = vv1->array[2*i];
        t2 = vv1->array[2*i+1];
        vv1->array[2*i]= t1*tm1->array[2*i]-t2*tm1->array[2*i+1];
        vv1->array[2*i+1]= t2*tm1->array[2*i]+t1*tm1->array[2*i+1];
    }*/
}
//fft_real(vv1, 2*kmax, 1);
pp = log(Spot / minmax);
i = 1;
while ((y->array[i] <= pp) && (i < Nx))
{
    i++;
}
i = i - 1;
//Price, quadratic interpolation
Sl = minmax * exp(y->array[i - 1]);
Sm = minmax * exp(y->array[i]);
Sr = minmax * exp(y->array[i + 1]);

```

```

        // S0 is between Sm and Sr
        pricel = minmax * vv1->array[i - 1];
        pricem = minmax * vv1->array[i];
        pricer = minmax * vv1->array[i + 1];
        //quadratic interpolation
        A = pricel;
        B = (pricem - pricel) / (Sm - Sl);
        C = (pricer - A - B * (Sr - Sl)) / (Sr - Sl) / (Sr - Sm);
        //Price
        price = A + B * (Spot - Sl) + C * (Spot - Sl) * (Spot - Sm);
        delta = B + C * (2 * Spot - Sl - Sm);

        *ptprice = *ptprice + coef->array[n] * price;
        *ptdelta = *ptdelta + coef->array[n] * delta;
        n++;
    }//=====END LOOP in n
// if(*ptprice<0) {*ptprice=0.0;}
if (ifCall == 0)
{
    *ptprice = *ptprice * log(2.0) / T - Spot / exp(divid * T) + minmax / exp(
    *ptdelta = *ptdelta * log(2.0) / T - 1 / exp(divid * T);
}
else
{
    *ptprice = Spot / exp(divid * T) - minmax / exp(r * T) + *ptprice * log(2.
    *ptdelta = 1.0 / exp(divid * T) + *ptdelta * log(2.0) / T;
}

//=====END=====
/*Memory desallocation*/
pnl_vect_free(&y);
pnl_vect_free(&vv1);
pnl_vect_free(&vv0);
pnl_vect_free(&tp1);
pnl_vect_free(&alin1);
pnl_vect_free(&tm1);
pnl_vect_free(&al1);
pnl_vect_free(&coef);

return OK;

```

```

}
int lookback_fxs(int model, double mu, double qu, double om, int ifCall, double
                double num, double nup, double cnum, double cnum,
                double r, double divid, double Strike,
                double T, double h,
                double er, double *ptprice, double *ptdelta)
{

    PnlVect *y, *vv0, *vv1, *tp1, *tm1, *coef, *alin1, *all1;
    long int N1 = 0, Nx, kmax, j;
    double pp;
    double a2_1 = 0.;
    int nn, n; //Laplace gs
    long int i;
    long int k;
    long int Nmax;
    double dt;

    double q;
    double mu1, str = 0., kx;
    double Sl, Sm, Sr;
    double pricel, pricem, pricer;
    double price, delta;
    double A, B, C;
    double sigma;

    k = 64;

    kx = er * log(2.0) / h;
    while (k < kx)
    {
        k = k * 2;
    }
    kmax = k;

    nn = 14;    //gs
    // N1=step;
    Nmax = 2 * kmax;

    //Memory allocation for space grid
    y = pnl_vect_create_from_zero(Nmax + 1); //space grid points

```

```

vv0 = pnl_vect_create_from_zero(Nmax + 1);
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
al1 = pnl_vect_create_from_zero(2 * kmax + 2);
alin1 = pnl_vect_create_from_zero(2 * kmax + 2);
tp1 = pnl_vect_create_from_zero(2 * kmax + 2);
tm1 = pnl_vect_create_from_zero(2 * kmax + 2);
coef = pnl_vect_create_from_zero(nn + 1); // gs

lp1 += om;
lm1 += om;
q = qu;

//===== compute coefficients
if (model == 1)
{
    mu1 = 0;
    sigma = 0.;
}
/*if(model == 2){
    mu1=mu;
    sigma=0.;
}
if(model == 3){
    mu1=0.0;
    sigma=0.;
    if((mu>0.0)&&(mu<0.1)) {mu1=mu-0.1;}
    if((mu<=0.0)&&(mu>-0.1)) {mu1=mu+0.1;}
    q+= mu1*om;
}*/
if (model == 4) /*KOU*/
{
    mu1 = 0.0; //mu

    sigma = nup;
    mu += sigma * sigma * om;
    nup = num;
    cnum *= (lm1 - om) / lm1;
    cnup *= (lp1 - om) / lp1;
}
Strike = Strike / minmax;

```

```

if (ifCall == 0)
{
    str = Strike - 1;
    if (str < 0)
    {
        str = 0.0;
    }
    for (j = 0; j < Nmax; j++)
    {
        y->array[j] = (j - kmax) * h;
        if (y->array[j] > 0)
        {
            vv0->array[j] = 0;
        }
        else
        {
            vv0->array[j] = Strike - exp(y->array[j]);
            if (vv0->array[j] < 0)
            {
                vv0->array[j] = 0.0;
            }
            vv0->array[j] = vv0->array[j] - str;
        }
    }
}
if (ifCall == 1)
{
    str = 1 - Strike;
    if (str < 0)
    {
        str = 0.0;
    }
    for (j = 0; j < Nmax; j++)
    {
        y->array[j] = (j - kmax) * h;
        if (y->array[j] < 0)
        {
            vv0->array[j] = 0;
        }
    }
}

```

```

        else
        {
            vv0->array[j] = exp(y->array[j]) - Strike;
            if (vv0->array[j] < 0)
            {
                vv0->array[j] = 0.0;
            }
            vv0->array[j] = vv0->array[j] - str;
        }
    }

fft_real(vv0, 2 * kmax, -1);

//-----weights-----
coef->array[1] = 0.00277778;
coef->array[2] = -6.40277778;
coef->array[3] = 924.05000000;
coef->array[4] = -34597.92777778;
coef->array[5] = 540321.11111111;
coef->array[6] = -4398346.36666666;
coef->array[7] = 21087591.77777770;
coef->array[8] = -63944913.04444440;
coef->array[9] = 127597579.55000000;
coef->array[10] = -170137188.08333300;
coef->array[11] = 150327467.03333300;
coef->array[12] = -84592161.50000000;
coef->array[13] = 27478884.76666660;
coef->array[14] = -3925554.96666666;
//-----
*ptprice = 0;
*ptdelta = 0;

//-----loop in weighted
for (n = 1; n <= nn;) // for(n=1; n<=nn;)
{
    /*Time step*/
    dt = T / (log(2.0) * n); //gs
// cout<<dt<<endl;
    q = qu + 1 / dt;

```



```

        findcoefnew(model, mu - mu1, sigma, lm1, lp1, num, nup, cnum, cnup, q, r,
//=====
// a2_1=q*dt;
    a2_1 = q;

    Nx = Nmax; /*number of space points*/

    for (i = 0; i < 2 * kmax; i++) alin1->array[i] = al1->array[i + 1];

    if (model == 1)
    {
        /*TSL*/ findfactor(0.0, 0.0, h, kmax, lp1, lm1, alin1, tp1, tm1);
    }
    if (model == 4)
    {
        /*KOU*/ findfactor(2.0, 2.0, h, kmax, lp1, lm1, alin1, tp1, tm1);
    }

//if(model == 1){/*TSL*/ factorslb(lm1, lp1, h, 0.0, 0.0, kmax, alin1, tp1);}
//if(model == 4){/*KOU*/ factorslb(lm1, lp1, h, 2.0, 2.0, kmax, alin1, tp1);}
//=====
    if (ifCall == 0)
    {
        for (i = 0; i < Nmax; i++)
        {
            tp1->array[i] = tp1->array[i] / a2_1;
            vv1->array[i] = vv0->array[i];
        }
        expectation(kmax, vv1, tp1);
        /* vv1->array[0]= vv1->array[0]*tp1->array[0];
        vv1->array[1]= vv1->array[1]*tp1->array[1];

        for(i = 1; i <= kmax-1; i++)
        {
            t1 = vv1->array[2*i];
            t2 = vv1->array[2*i+1];
            vv1->array[2*i]= t1*tp1->array[2*i]-t2*tp1->array[2*i+1];
            vv1->array[2*i+1]= t2*tp1->array[2*i]+t1*tp1->array[2*i+1];
        }*/
    }
}

```

```

if (ifCall == 1)
{
    for (i = 0; i < Nmax; i++)
    {
        tm1->array[i] = tm1->array[i] / a2_1;
        vv1->array[i] = vv0->array[i];
    }
    expectation(kmax, vv1, tm1);
    /*vv1->array[0]= vv1->array[0]*tm1->array[0];
    vv1->array[1]= vv1->array[1]*tm1->array[1];

    for(i = 1; i <= kmax-1; i++)
    {
        t1 = vv1->array[2*i];
        t2 = vv1->array[2*i+1];
        vv1->array[2*i]= t1*tm1->array[2*i]-t2*tm1->array[2*i+1];
        vv1->array[2*i+1]= t2*tm1->array[2*i]+t1*tm1->array[2*i+1];
    }*/
}
// fft_real(vv1, 2*kmax, 1);
pp = log(Spot / minmax);
i = 1;
while ((y->array[i] <= pp) && (i < Nx))
{
    i++;
}
i = i - 1;
//Price, quadratic interpolation
S1 = minmax * exp(y->array[i - 1]);
Sm = minmax * exp(y->array[i]);
Sr = minmax * exp(y->array[i + 1]);

// S0 is between Sm and Sr
pricel = minmax * vv1->array[i - 1];
pricem = minmax * vv1->array[i];
pricer = minmax * vv1->array[i + 1];
//quadratic interpolation
A = pricel;
B = (pricem - pricel) / (Sm - S1);
C = (pricer - A - B * (Sr - S1)) / (Sr - S1) / (Sr - Sm);
//Price

```

```

    price = A + B * (Spot - S1) + C * (Spot - S1) * (Spot - Sm);
    delta = B + C * (2 * Spot - S1 - Sm);

    *ptprice = *ptprice + coef->array[n] * price;
    *ptdelta = *ptdelta + coef->array[n] * delta;
    n++;
} //=====END LOOP in n
// if(*ptprice<0) {*ptprice=0.0;}
//if(ifCall==1)
//{*ptprice=*ptprice*log(2.0)/T+minmax/exp(r*T)*str;
//    *ptdelta=*ptdelta*log(2.0)/T;
//}
//else
//{*ptprice=str*minmax/exp(r*T)+*ptprice*log(2.0)/T;
//    *ptdelta=*ptdelta*log(2.0)/T;
//}
    *ptprice = str * minmax / exp(r * T) + *ptprice * log(2.0) / T;
    *ptdelta = *ptdelta * log(2.0) / T;
    //=====END=====
    /*Memory desallocation*/
    pnl_vect_free(&y);
    pnl_vect_free(&vv1);
    pnl_vect_free(&vv0);
    pnl_vect_free(&tp1);
    pnl_vect_free(&alin1);
    // pnl_vect_free( tbp1);
    // pnl_vect_free( ltp1);
    // pnl_vect_free( ltm1);
    // pnl_vect_free( tb1);
    // pnl_vect_free( tbm1);
    pnl_vect_free(&tm1);
    pnl_vect_free(&al1);
    pnl_vect_free(&coef);
    // pnl_vect_free( t);
    return OK;
}

int swing(int model, double mu, double qu, double om,
          int ifCall, double Spot, double lm1, double lp1,
          double num, double nup, double cnum, double cnup,
          double r, double divid,
          double T, double h, double Strike1, double del, int Nd,

```

```

        double er, long int step,
        double *ptprice, double *ptdelta)
{
    PnlVect *t, *y, * v1, *gg, *G, *vv1, *tp1, *tm1, *eomcut,
        *alin1, *eom, *reb, *switcharrow, *al1, *bl1;
    int dims[3], tab[3];
    PnlHmat *Price;
    long int N1 = 0, Nx, kmax, j, L, n, r_index, k_index;

    double pp;
    double t1, t2;

    double a2_1 = 0.;
    long int i;
    long int k;
    long int Nmax, N01;
    double dt;
    double q;
    double kx;
    double Sl, Sm, Sr;
    double pricel, pricem, pricer;
    double A, B, C;
    double sigma;
    double flagCall;
    flagCall = ifCall ? 1.0 : -1.0; // 1.0 for Call, -1.0 for Put

    if (ifCall == 0) //IF PUT
    {
        if (Spot >= 0.8 * Strike1 * exp(er * log(2.)))
        {
            *ptprice = 0.;
            *ptdelta = 0.;
            printf("Spot is out of range. Increase scale parameter \ n");
            return OK;
        }
        if (Spot <= 1.2 * Strike1 * exp(-er * log(2.)))
        {
            *ptprice = Strike1 - Spot;
            *ptdelta = -1.0;
            printf("Spot is out of range. Increase scale parameter \ n");

```

```

        return OK;
    }
}
else
{
    if (Spot >= 0.8 * Strike1 * exp(er * log(2.)))
    {
        *ptprice = - Strike1 + Spot;
        *ptdelta = 1.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
    if (Spot <= Strike1 * exp(-er * log(2.)) * 1.2)
    {
        *ptprice = 0.;
        *ptdelta = 0.;
        printf("Spot is out of range. Increase scale parameter \ n");
        return OK;
    }
}
}

```

```

k = 64;

```

```

kx = er * log(2.0) / h;
while (k < kx)
{
    k = k * 2;
}

```

```

kmax = k;

```

```

N1 = step;
Nmax = 2 * kmax;
N01 = kmax;

```

```

//Memory allocation for space grid
y = pnl_vect_create(Nmax + 1); //space grid points
v1 = pnl_vect_create(Nmax + 1); //prices at previous time step
gg = pnl_vect_create(2 * kmax + 2); //payoff
vv1 = pnl_vect_create(2 * kmax + 2);
tp1 = pnl_vect_create(2 * kmax + 2);
alin1 = pnl_vect_create(2 * kmax + 2);

```

```

tm1 = pnl_vect_create(2 * kmax + 2);
al1 = pnl_vect_create(2 * kmax + 2);
bl1 = pnl_vect_create(2 * kmax + 2);
eom = pnl_vect_create(Nmax + 1);
eomcut = pnl_vect_create(Nmax + 1);
reb = pnl_vect_create(Nmax + 1);
G = pnl_vect_create(Nmax + 1);
t = pnl_vect_create(N1 + 2); //time points


dims[0] = N1 + 1;
dims[1] = Nd + 1;
dims[2] = Nmax + 1;
Price = pnl_hmat_create(3, dims);


/*Time step*/
dt = T / N1;
/*First index where i*t<t-r_period*/
for (n = 0; n <= N1; n++)
{
    t->array[n] = n * dt;
}
// int M=Ntime;

// mat_index=M;
i = N1;
do
{
    i--;
}
while (t->array[i] > (T - del) + 0.00000001);

r_index = i;
k_index = N1 - r_index;


lp1 += om;
lm1 += om;

```

```

q = qu + 1 / dt;

//===== compute coefficients
if (model == 1) /*TSL*/
{
    q = q - mu * om;
    sigma = 0.;
}
if (model == 4) /*KOU*/
{
    sigma = nup;
    mu += sigma * sigma * om;
    nup = num;
    cnum *= (lm1 - om) / lm1;
    cnup *= (lp1 - om) / lp1;
}
if (model == 5) /*Merton*/
{
    sigma = num; //nup=p0; cnum=lambda;cnup=gam0;
    mu += sigma * sigma * om; // change for non-zero om!!!
//cnum*=(lm1-om)/lm1;
//cnup*=(lp1-om)/lp1;
    num = 2.0;
}
findcoef_sw(model, mu, sigma, lm1, lp1, num, nup, cnum, cnup, q, r, T, h, kmax
//=====

a2_1 = q * dt;
if (model == 1) /*TSL*/
{
    nup = 0.0;
    num = 0.0;
}
if (model == 5) /*Merton*/
{
    nup = num;
}
Nx = Nmax; /*number of space points*/
//////////begin factors

```

```

for (i = 0; i < 2 * kmax; i++) alin1->array[i] = al1->array[i + 1];
findfactor(nup, num, h, kmax, lp1, lm1, alin1, tp1, tm1);

if (ifCall == 0)
{
    for (j = 0; j < Nmax; j++)
    {
        y->array[j] = (j - N01 - 0.5) * h;
        gg->array[j] = 0;
        eomcut->array[j] = 0;
        eom->array[j] = exp(om * y->array[j]);
        reb->array[j] = Strike1 * dt * r * eom->array[j];
    }
}
else
{
    for (j = 0; j < Nmax; j++)
    {
        y->array[j] = (j - N01 + 0.5) * h;
        gg->array[j] = 0;
        eomcut->array[j] = 0;
        eom->array[j] = exp(om * y->array[j]);
        reb->array[j] = -Strike1 * dt * r * eom->array[j];
    }
}

if (ifCall == 0)
{
    j = kmax;
    do
    {
        eomcut->array[j] = exp(y->array[j]) * eom->array[j];
        gg->array[j] = Strike1 * (eom->array[j] - eomcut->array[j]); //ok
        j--;
    }
    while (j >= 0);
}
else
{
    j = kmax;

```



```

do
{
    eomcut->array[j] = exp(y->array[j]) * eom->array[j];
    gg->array[j] = -Strike1 * (eom->array[j] - eomcut->array[j]); //ok
    j++;
}
while (j < Nmax);
}

//===== EXCHANGE tp AND tm ARRAYS FOR UP-OUT
if (ifCall == 1)
{
    switcharrow = tp1;
    tp1 = tm1;
    tm1 = switcharrow;
}

for (i = 0; i < 2 * kmax; i++)
{
    G->array[i] = Strike1 * flagCall * eom->array[i] * (exp(y->array[i]) - 1);
}
fft_real(G, 2 * kmax, -1);
expectation(kmax, G, tm1);

//=====
for (i = 0; i < Nmax; i++)
{
    tp1->array[i] = tp1->array[i] / a2_1;
}

//=====Loop in exercise possibilities=====
dims[0] = 0;
tab[1] = 0;
for (j = 0; j < Nd; j++)
{
    dims[1] = j;
    if (j > 0)
    {
        tab[1] = j - 1;
    }
    for (i = 0; i < 2 * kmax; i++)
    {

```

```

        vv1->array[i] = gg->array[i];
        reb->array[i] = G->array[i];

    }
    fft_real(vv1, 2 * kmax, -1);
    for (i = 0; i < Nmax; i++)
    {
        dims[2] = i; //Price[0][j][i]
        pnl_hmat_set(Price, dims, vv1->array[i]);
    }

//=====Main Loop on time grid=====

    for (L = 1; L < N1 + 1; L++)
    {
        dims[0] = L;
        //mut=t->array[L]*mu1;
        //emut=exp(-mut);

        vv1->array[0] = vv1->array[0] * tm1->array[0];
        vv1->array[1] = vv1->array[1] * tm1->array[1];

        for (i = 1; i <= kmax - 1; i++)
        {
            t1 = vv1->array[2 * i];
            t2 = vv1->array[2 * i + 1];
            vv1->array[2 * i] = t1 * tm1->array[2 * i] - t2 * tm1->array[2 * i + 1];
            vv1->array[2 * i + 1] = t2 * tm1->array[2 * i] + t1 * tm1->array[2 * i + 1];
        }
        fft_real(vv1, 2 * kmax, 1);
        tab[0] = L - k_index;
        if ((L > k_index - 1) && (j > 0))
        {
            for (i = 0; i < 2 * kmax; i++)
            {
                tab[2] = i;
                reb->array[i] = pnl_hmat_get(Price, tab);
            } //pnl_hmat_get(Price,L-k_index,j-1,i);
            expectation(kmax, reb, bl1);
            fft_real(reb, 2 * kmax, -1);
        }
    }

```

```

        expectation(kmax, reb, tm1);
    for (i = 0; i < 2 * kmax; i++)
    {
        reb->array[i] = reb->array[i] + G->array[i];
    }
}

i = Nmax - 1;
do
{
    if (vv1->array[i] < reb->array[i])
    {
        vv1->array[i] = reb->array[i];
    }
    i--;
}
while (i >= 0);

fft_real(vv1, 2 * kmax, -1);

vv1->array[0] = vv1->array[0] * tp1->array[0];
vv1->array[1] = vv1->array[1] * tp1->array[1];

for (i = 1; i <= kmax - 1; i++)
{
    t1 = vv1->array[2 * i];
    t2 = vv1->array[2 * i + 1];
    vv1->array[2 * i] = t1 * tp1->array[2 * i] - t2 * tp1->array[2 * i + 1];
    vv1->array[2 * i + 1] = t2 * tp1->array[2 * i] + t1 * tp1->array[2 * i + 1];
}
for (i = 0; i < Nmax; i++)
{
    dims[2] = i; //pnl_hmat_set(Price, L, j, i, vv1->array[i]);
    pnl_hmat_set(Price, dims, vv1->array[i]);
}
} // ===== END MAIN LOOP =====
} //end of exercise loop
fft_real(vv1, 2 * kmax, 1);

```

```

if (ifCall == 0)
{
    for (i = 0; i < Nmax; i++)
    {
        y->array[i] = y->array[i];
        v1->array[i] = vv1->array[i] / eom->array[i];
    }
}
else
{
    for (i = 0; i < Nmax; i++)
    {
        y->array[i] = y->array[i];
        v1->array[i] = vv1->array[i] / eom->array[i];
    }
}

pp = log(Spot / Strike1);

i = 1;

while ((y->array[i] <= pp) && (i < Nx))
{
    i++;
}
i = i - 1;
//Price, quadratic interpolation
S1 = Strike1 * exp(y->array[i - 1]);
Sm = Strike1 * exp(y->array[i]);
Sr = Strike1 * exp(y->array[i + 1]);

// S0 is between Sm and Sr
pricel = v1->array[i - 1];
pricem = v1->array[i];
pricer = v1->array[i + 1];

//quadratic interpolation
A = pricel;
B = (pricem - pricel) / (Sm - S1);
C = (pricer - A - B * (Sr - S1)) / (Sr - S1) / (Sr - Sm);

```

```

//Price
*ptprice = A + B * (Spot - S1) + C * (Spot - S1) * (Spot - Sm);
if (*ptprice < 0)
{
    *ptprice = 0.0;
}
//Delta
*ptdelta = B + C * (2 * Spot - S1 - Sm);

//=====END=====
/*Memory desallocation*/
pnl_vect_free(&y);
pnl_vect_free(&v1);
pnl_vect_free(&gg);
pnl_vect_free(&vv1);
pnl_vect_free(&tp1);
pnl_vect_free(&alin1);
pnl_vect_free(&tm1);
pnl_vect_free(&a11);
pnl_vect_free(&b11);
pnl_vect_free(&eom);
pnl_vect_free(&eomcut);
pnl_vect_free(&reb);
pnl_vect_free(&G);
pnl_vect_free(&t);
pnl_hmat_free(&Price);
return OK;
}
//////////////////////////////////VAR and CTE//////////////////////////////////

int var_fft(int model, double mu,
            double Spot, double lm1, double lp1,
            double num, double nup, double cnum, double cnu,
            double T, double h, double Strike1, double er, double alpha,
            double *ptprice, double *ptdelta)
{
    PnlVect *y, *vv1, *a11;
    long int kmax, j;

```

```

double kx;
long int i;
long int k;
long int Nmax;

k = 64;

kx = er * log(4) / h;
while (k < kx)
{
    k = k * 2;
}
kmax = k;

Nmax = 2 * kmax;

//Memory allocation for space grid
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points
vv1 = pnl_vect_create_from_zero(2 * kmax + 2);
all = pnl_vect_create_from_zero(2 * kmax + 2);

//////////space grid//////////
for (j = 0; j < Nmax; j++)
{
    y->array[j] = (j - kmax) * h;
}

//===== compute coefficients for chf
findcoef_var(1, mu, 0., lm1, lp1, num, nup, cnum, cnup, 0., T, h, kmax, 1, all)
//=====

//////////recover probabilities//////////
vv1->array[0] = 1.;
vv1->array[1] = 1.;

i = 1;
j = 1;

```

```

do
{
    j = -j;
    vv1->array[2 * i] = j;
    vv1->array[2 * i + 1] = 0.;
    i++;
}
while (i < kmax);

expectation(kmax, vv1, al1);

////////////////////////////////compute VaR////////////////////////////////

kx = 0.;
i = 0;
while ((kx < alpha) && (i < Nmax - 1))
{
    kx = kx + vv1->array[i];
    i = i + 1;
}
i = i - 1;
//VaR
*ptprice = Spot * exp(y->array[i]) - Strike1;

////////////////////////////////compute CTE////////////////////////////////
*ptdelta = 0;
while (i < Nmax)
{
    *ptdelta = *ptdelta + vv1->array[i] * exp(y->array[i]);
    i = i + 1;
}
//CTE
*ptdelta = *ptdelta * Spot / (1 - alpha) - Strike1;

//=====END=====
/*Memory desallocation*/
pnl_vect_free(&y);
pnl_vect_free(&vv1);

```

```

    pnl_vect_free(&a11);
    return OK;
}

```

////////////////////////////////////Monte Carlo methods////////////////////////////////////

```

int froot(long int kmax, PnlVect * F, double Fx, long int *k0, long int *k1)
{
    long int k;
    *k0 = 0; *k1 = kmax;
    if (Fx <= GET(F, 0)){ *k1 = *k0; }
    while (*k1 > *k0 + 1)
    {
        k = (int)(*k0 + *k1) / 2;
        if (Fx > GET(F, k)){ *k0 = k; }
        else { *k1 = k; }
    }

    return 1;
}

```

```

int frootm(long int kmax, PnlVect * F, double Fx, long int *k0, long int *k1)
{
    long int k;
    *k0 = 0; *k1 = kmax;
    if (Fx >= GET(F, 0)){ *k1 = *k0; }
    while (*k1 > *k0 + 1)
    {
        k = (int)(*k0 + *k1) / 2;
        if (Fx < GET(F, k)){ *k0 = k; }
        else { *k1 = k; }
    }

    return 1;
}

```

```

int TSL_lookbackfixed_WHMC(int ifCall, double S0, double K, double s_maxmin, dou
T, double r, double divid, double lm1, double lp1, double num, double nup, doubl
int generator, int n_paths, double *ptPrice, double *priceError)
{

```



```

double cnup, cnum, lpnu, lmnu, mu, qu, q, om, kx;
double payoff, sum_payoff, sum_square_payoff, var_payoff;
double discount, payoff_pref;
long int i, kmax, Nmax, k0, k1, kmin;
int j, nn, n;
double Vn, Sn; //
double dt; // time variables
PnlVect *coef;
PnlVect *vv0, *vv1, *y, *eom, *Fp, *Fm, *tp1, *tm1, *alin1, *al1;
PnlRng *rng;
//{om=lm1<-2. ? 2. : (-lm1+1.)/2.; }
om = 0.;
cnup = cp*pnl_tgamma(-nup);
cnum = cm*pnl_tgamma(-num);

lpnu = exp(nup*log(lp1));
lmnu = exp(num*log(-lm1));

mu = r - divid + cnup*(lpnu - exp(nup*log(lp1 + 1.0))) + cnum*(lmnu - exp(num*log(-lm1 + 1.0)));
qu = (pow(lp1, nup) - pow(lp1 + om, nup))*cnup + (pow(-lm1, num) - pow(-lm1 - om, num))*cnum;
nn = 14;
Vn = 0;
discount = exp(-r*T);

sum_payoff = 0;
sum_square_payoff = 0;
if (ifCall == 0) // IF PUT - lookback fixed strike put
{
    payoff_pref = MAX(K - s_maxmin, 0);
}
else //IF CALL - lookback fixed strike call
{
    payoff_pref = MAX(s_maxmin - K, 0);
}

rng = pnl_rng_create(generator);
// rng must be initialized. //
pnl_rng_sseed(rng, 0);

```

```

j = 64;
kx = er*log(2.0) / h;
while (j<kx)
{
j = j * 2;
}
kmax = j;
Nmax = 2 * kmax;// the number of the space points for the cdfs

//Memory allocation for space grid

coef = pnl_vect_create_from_zero(nn + 1);
y = pnl_vect_create_from_zero(Nmax + 1);//space grid points
eom = pnl_vect_create_from_zero(Nmax + 1);//space grid points
vv0 = pnl_vect_create_from_zero(Nmax + 1);//payoff
vv1 = pnl_vect_create_from_zero(Nmax + 1);//intermediate function
Fp = pnl_vect_create_from_zero(kmax);// CDF for the Plus WH-factor
Fm = pnl_vect_create_from_zero(kmax);// CDF for the Plus WH-factor
al1 = pnl_vect_create_from_zero(2 * kmax + 2);
alin1 = pnl_vect_create_from_zero(2 * kmax + 2);
tp1 = pnl_vect_create_from_zero(2 * kmax + 2);
tm1 = pnl_vect_create_from_zero(2 * kmax + 2);

lp1 += om; // parameters shift to calculate CDFs for Plus and Minus WH-factors
lm1 += om; //

//////////cdfs calculations//////////
for (j = 1; j <= kmax; j++)
{
y->array[j] = (j - kmax)*h;
vv0->array[j - 1] = 0;
eom->array[j] = exp(-om*y->array[j]);
}
j = kmax + 1;
do
{
y->array[j] = (j - kmax)*h;
eom->array[j] = exp(-om*y->array[j]);
vv0->array[j - 1] = -eom->array[j];
j++;

```

```
} while (j <= Nmax);
```

```
fft_real(vv0, 2 * kmax, -1);
```

```
for (i = 0; i<kmax; i++)
{
Fm->array[i] = 0;
Fp->array[i] = 0;
}
```

```
//-----weights-----
```

```
coef->array[1] = 0.00277778;
coef->array[2] = -6.40277778;
coef->array[3] = 924.05000000;
coef->array[4] = -34597.92777778;
coef->array[5] = 540321.11111111;
coef->array[6] = -4398346.36666666;
coef->array[7] = 21087591.77777770;
coef->array[8] = -63944913.04444440;
coef->array[9] = 127597579.55000000;
coef->array[10] = -170137188.08333300;
coef->array[11] = 150327467.03333300;
coef->array[12] = -84592161.50000000;
coef->array[13] = 27478884.76666660;
coef->array[14] = -3925554.96666666;
```

```
//-----
```

```
//-----loop in weighted
```

```
for (n = 1; n <= 14;) // for(n=1; n<=nn;)
{
//Time step//
dt = T / (log(2.0)*n); //the Gaver-Stehfest algorithm parameter
q = qu + 1 / dt;
findcoef_mc(1, mu, 0, lm1, lp1, num, nup, cnum, cnup, q, r, T, h, kmax, er, 14,
//=====
```

```

for (i = 0; i<2 * kmax; i++)
{
    alin1->array[i] = al1->array[i + 1];
}

//TSL//
findfactor(0.0, 0.0, h, kmax, lp1, lm1, alin1, tp1, tm1);

//===== EXCHANGE tp AND tm ARRAYS FOR UP-OUT
if (ifCall == 1) //////////check
{
    tp1 = pnl_vect_copy(tm1);
    // alin1 = tp1;
    // tp1 = tm1;
    // tm1 = alin1;
}
//=====

for (i = 0; i<Nmax; i++)
{
    tp1->array[i] = tp1->array[i] / q;
    vv1->array[i] = vv0->array[i];
}

expectation(kmax, vv1, tp1);

for (i = 1; i<Nmax + 1; i++)
{
    vv1->array[i - 1] = vv1->array[i - 1] / eom->array[i];
}

if (ifCall == 0)// IF PUT
{
    for (i = 0; i<kmax; i++)
    {
        Fm->array[i] = Fm->array[i] + coef->array[n] * vv1->array[kmax + i - 1];
    }
}
else //IF Call

```

```

{
for (i = 0; i<kmax; i++)
{
Fp->array[i] = Fp->array[i] + coef->array[n] * vv1->array[kmax - i - 1];
}
}
n++;
}//=====END LOOP in n
kmin = kmax - 1;
if (ifCall == 0)// IF PUT
{
for (i = kmax - 1; i>0; i--){ Fm->array[i] = Fm->array[i] * log(2.0) / T + 1.; i
Fm->array[0] = 1.;
}
else
{
for (i = 0; i<kmax; i++){ Fp->array[i] = Fp->array[i] * log(2.0) / T + 1.; if (F
// Fp->array[0]=0.;
}
}
//////////end cdfs calculations//////////

//////////Monte Carlo simulation//////////
sum_payoff = 0;
sum_square_payoff = 0;
if (ifCall == 0)//PUT
{
for (i = 0; i<n_paths; i++)
{
Sn = pnl_rng_uni(rng);
frootm(kmin, Fm, Sn, &k0, &k1);
if (k1 == 0){ Vn = 0.0; }
else{ Vn = -GET(y, kmax + k0) - h*(Sn - GET(Fm, k0)) / (GET(Fm, k1) - GET(Fm, k0));
payoff = MAX(K - S0*exp(Vn), payoff_pref);
sum_payoff += payoff;
sum_square_payoff += payoff*payoff;
}
}
}
else//CALL
{
for (i = 0; i<n_paths; i++)

```

```

{
  Sn = pnl_rng_uni(rng);
  froot(kmin, Fp, Sn, &k0, &k1);
  if (k1 == 0){ Vn = 0.0; }
  else{ Vn = GET(y, kmax + k0) + h*(Sn - GET(Fp, k0)) / (GET(Fp, k1) - GET(Fp, k0));
  payoff = MAX(S0*exp(Vn) - K, payoff_pref);
  sum_payoff += payoff;
  sum_square_payoff += payoff*payoff;
}
}

var_payoff = (sum_square_payoff - sum_payoff*sum_payoff / n_paths) / (n_paths -
*ptPrice = discount*sum_payoff / n_paths;
*priceError = 1.96*discount*sqrt(var_payoff) / sqrt((double)n_paths);

// Frees the generator //
pnl_rng_free(&rng);
// Frees vectors //
pnl_vect_free(&coef);
pnl_vect_free(&y);
pnl_vect_free(&eom);
pnl_vect_free(&vv0);
pnl_vect_free(&vv1);
pnl_vect_free(&Fp);
pnl_vect_free(&Fm);
pnl_vect_free(&a11);
pnl_vect_free(&alin1);
pnl_vect_free(&tp1);
pnl_vect_free(&tm1);
return OK;
}

int TSL_lookbackfloat_WHMC(int ifCall, double S0, double s_maxmin, double
T, double r, double divid, double lm1, double lp1, double num, double nup, doubl
int generator, int n_paths, double *ptPrice, double *priceError)
{

double cnup, cnum, lpnu, lmnu, mu, qu, q, om, kx;
double payoff, sum_payoff, sum_square_payoff, var_payoff;
double discount, payoff_pref;
long int i, kmax, Nmax, k0, k1, kmin;
int j, nn, n;

```

```

double Vn, Sn; //
double dt; // time variables
PnlVect *coef;
PnlVect *vv0, *vv1, *y, *eom, *Fp, *Fm, *tp1, *tm1, *alin1, *al1;
PnlRng *rng;
//{om=lm1<-2. ? 2. : (-lm1+1.)/2.; }
om = 0.;
cnup = cp*pnl_tgamma(-nup);
cnum = cm*pnl_tgamma(-num);

lpnu = exp(nup*log(lp1));
lmnu = exp(num*log(-lm1));

mu = r - divid + cnup*(lpnu - exp(nup*log(lp1 + 1.0))) + cnum*(lmnu - exp(num*log(-lm1 + 1.0)));
qu = (pow(lp1, nup) - pow(lp1 + om, nup))*cnup + (pow(-lm1, num) - pow(-lm1 - om, num))*cnum;
nn = 14;
Vn = 0;
discount = exp(-r*T);

sum_payoff = 0;
sum_square_payoff = 0;
if (ifCall == 0) // IF PUT - lookback floating strike put
{
payoff_pref = s_maxmin / S0; //MAX(K - s_maxmin, 0);
}
else //IF CALL - lookback fixed strike call
{
payoff_pref = s_maxmin / S0; //MAX(K - s_maxmin, 0);
}

rng = pnl_rng_create(generator);
/* rng must be initialized. */
pnl_rng_sseed(rng, 0);

j = 64;
kx = er*log(2.0) / h;
while (j<kx)
{
j = j * 2;
}

```

```

}
kmax = j;
Nmax = 2 * kmax; // the number of the space points for the cdfs

//Memory allocation for space grid

coef = pnl_vect_create_from_zero(nn + 1);
y = pnl_vect_create_from_zero(Nmax + 1); //space grid points
eom = pnl_vect_create_from_zero(Nmax + 1); //space grid points
vv0 = pnl_vect_create_from_zero(Nmax + 1); //payoff
vv1 = pnl_vect_create_from_zero(Nmax + 1); //intermediate function
Fp = pnl_vect_create_from_zero(kmax); // CDF for the Plus WH-factor
Fm = pnl_vect_create_from_zero(kmax); // CDF for the Plus WH-factor
all = pnl_vect_create_from_zero(2 * kmax + 2);
alin1 = pnl_vect_create_from_zero(2 * kmax + 2);
tp1 = pnl_vect_create_from_zero(2 * kmax + 2);
tm1 = pnl_vect_create_from_zero(2 * kmax + 2);

lp1 += om; // parameters shift to calculate CDFs for Plus and Minus WH-factors
lm1 += om; //

////////////////////cdfs calculations////////////////////
for (j = 1; j <= kmax; j++)
{
y->array[j] = (j - kmax)*h;
vv0->array[j - 1] = 0;
eom->array[j] = exp(-om*y->array[j]);
}
j = kmax + 1;
do
{
y->array[j] = (j - kmax)*h;
eom->array[j] = exp(-om*y->array[j]);
vv0->array[j - 1] = -eom->array[j];
j++;
} while (j <= Nmax);

fft_real(vv0, 2 * kmax, -1);

for (i = 0; i < kmax; i++)

```



```

{
Fm->array[i] = 0;
Fp->array[i] = 0;
}

//-----weights-----

coef->array[1] = 0.00277778;
coef->array[2] = -6.40277778;
coef->array[3] = 924.05000000;
coef->array[4] = -34597.92777778;
coef->array[5] = 540321.11111111;
coef->array[6] = -4398346.36666666;
coef->array[7] = 21087591.77777770;
coef->array[8] = -63944913.04444440;
coef->array[9] = 127597579.55000000;
coef->array[10] = -170137188.08333300;
coef->array[11] = 150327467.03333300;
coef->array[12] = -84592161.50000000;
coef->array[13] = 27478884.76666660;
coef->array[14] = -3925554.96666666;
//-----

//-----loop in weighted
for (n = 1; n <= 14;) // for(n=1; n<=nn;)
{
/*Time step*/
dt = T / (log(2.0)*n); //the Gaver-Stehfest algorithm parameter
q = qu + 1 / dt;
findcoef_mc(1, mu, 0, lm1, lp1, num, nup, cnum, cnup, q, r, T, h, kmax, er, 14,
//=====

for (i = 0; i<2 * kmax; i++)
{
alin1->array[i] = al1->array[i + 1];
}

/*TSL*/

```

```

findfactor(0.0, 0.0, h, kmax, lp1, lm1, alin1, tp1, tm1);

//===== EXCHANGE tp AND tm ARRAYS FOR UP-OUT
if (ifCall == 0) //////////check
{
tp1=pnl_vect_copy(tm1);
// alin1 = tp1;
// tp1 = tm1;
// tm1 = alin1;
}
//=====

for (i = 0; i<Nmax; i++)
{
tp1->array[i] = tp1->array[i] / q;
vv1->array[i] = vv0->array[i];
}

expectation(kmax, vv1, tp1);

for (i = 1; i<Nmax + 1; i++)
{
vv1->array[i - 1] = vv1->array[i - 1] / eom->array[i];
}

if (ifCall == 1)// IF CALL
{
for (i = 0; i<kmax; i++)
{
Fm->array[i] = Fm->array[i] + coef->array[n] * vv1->array[kmax + i - 1];
}
}
else //IF PUT
{
for (i = 0; i<kmax; i++)
{
Fp->array[i] = Fp->array[i] + coef->array[n] * vv1->array[kmax - i - 1];
}
}
}

```

```

n++;
}//=====END LOOP in n
kmin = kmax - 1;
if (ifCall == 1)// IF CALL
{
for (i = kmax - 1; i>0; i--){ Fm->array[i] = Fm->array[i] * log(2.0) / T + 1.; i
Fm->array[0] = 1.;
}
else // IF PUT
{
for (i = 0; i<kmax; i++){ Fp->array[i] = Fp->array[i] * log(2.0) / T + 1.; if (F
// Fp->array[0]=0.;
}
}
//////////end cdfs calculations//////////

//////////Monte Carlo simulation//////////
sum_payoff = 0;
sum_square_payoff = 0;
if (ifCall == 1)//CALL
{
for (i = 0; i<n_paths; i++)
{
Sn = pnl_rng_uni(rng);
frootm(kmin, Fm, Sn, &k0, &k1);
if (k1 == 0){ Vn = 0.0; }
else{ Vn = -GET(y, kmax + k0) - h*(Sn - GET(Fm, k0)) / (GET(Fm, k1) - GET(Fm, k0))
payoff = MIN(exp(Vn), payoff_pref);
sum_payoff += payoff;
sum_square_payoff += payoff*payoff;
}
*ptPrice = S0 - S0*discount*sum_payoff / n_paths;
}
else//PUT
{
for (i = 0; i<n_paths; i++)
{
Sn = pnl_rng_uni(rng);
froot(kmin, Fp, Sn, &k0, &k1);
if (k1 == 0){ Vn = 0.0; }
else{ Vn = GET(y, kmax + k0) + h*(Sn - GET(Fp, k0)) / (GET(Fp, k1) - GET(Fp, k0))

```

```

payoff = MAX(exp(Vn), payoff_pref);
sum_payoff += payoff;
sum_square_payoff += payoff*payoff;
}
*ptPrice = S0*discount*sum_payoff / n_paths - S0;
}
var_payoff = (sum_square_payoff - sum_payoff*sum_payoff / n_paths) / (n_paths -

*priceError = 1.96*S0*discount*sqrt(var_payoff) / sqrt((double)n_paths);

/* Frees the generator */
pnl_rng_free(&rng);
/* Frees vectors */
pnl_vect_free(&coef);
pnl_vect_free(&y);
pnl_vect_free(&eom);
pnl_vect_free(&vv0);
pnl_vect_free(&vv1);
pnl_vect_free(&Fp);
pnl_vect_free(&Fm);
pnl_vect_free(&a11);
pnl_vect_free(&alin1);
pnl_vect_free(&tm1);
pnl_vect_free(&tp1);
return OK;
}

#endif //PremiaCurrentVersion

```