Image Segmentation by Refinement
Reference manual

Version 1.2

Hend Ben Ameur ¡hbenameur@yahoo.ca¿Francois Clement ¡Francois.Clement@inria

2017-11-23

1   Installation of Ref-image

To install the Ref-image command, follow the instructions in the `INSTALL` file of the distribution, or use the generic instructions of the next section.

Ref-image is free software distributed under the 3-clause BSD license, see the `LICENSE` file for details.

2   For the users of the distributed version of your package

They should follow the directives of the `INSTALL` file of the distribution of your package.

2.1   To configure, build and install the package

```
./configure [<installation_root_directory>]
make
make install
```

When called with one argument, the `configure` script makes it the root directory for the installation. When called without argument, the `configure` script interactively asks the user.

The variable `installation_root_directory` stands for the directory where the project will be installed; it must contain a valid directory name where the user can write. All the files that are installed by your project will be copied into sub directories of this one. Namely:

- binaries go into the sub-directory
  `installation_root_directory/bin`,

- includes go into the sub-directory
  `installation_root_directory/include/<project_package_name>`,

- OCaml libraries go into the sub-directory
  `installation_root_directory/include/lib/ocaml/<project_package_name>`
  and other libraries go into the sub-directory
  `installation_root_directory/lib/<project_package_name>`,

- manual pages go into the sub-directory
  `installation_root_directory/man/man<man_section>`,

- (La)TeX documentations go into the sub-directory
  `installation_root_directory/share/doc/tex` and HTML documentation pages
  go into the sub-directory
  `installation_root_directory/share/doc/htm`,

- other materials go into the sub-directory
  `installation_root_directory/share/<project_package_name>`.

2.2   To clean and remove the package

To remove all files installed by `make install`, all files built by `make` and all files created
by `./configure`, respectively type in:

```
make uninstall
make clean
./unconfigure
```